



# Eurol ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 12/02/2014

Revision date: 26/02/2015

Supersedes: 12/02/2014

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Eurol ATF 6100  
Product code : E113657  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : industrial use, professional use, consumer use  
Use of the substance/mixture : lubricating oil: mineral product  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Eurol bv.  
Energiestraat 12  
7442 DA Nijverdal - The Netherlands  
T +31 548 615165  
[r.hilgers@eurol.com](mailto:r.hilgers@eurol.com) - [www.eurol.com](http://www.eurol.com)  
Eurol b.v.  
Energiestraat 12  
7442 DA Nijverdal  
The Netherlands  
Tel: +(31) (0) 548 615165  
e-mail: reach@eurol.com

#### 1.4. Emergency telephone number

Emergency number : +31 548 615165  
(Monday to Friday: 8:00 - 17:00)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children  
EUH-statements : EUH208 - Contains Alkoxylated long-chain alkyl amine. May produce an allergic reaction  
EUH210 - Safety data sheet available on request

#### 2.3. Other hazards

Other hazards not contributing to the classification : This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L)". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

PBT: not relevant – no registration required  
vPvB: not relevant – no registration required

# Eurol ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS No) 64742-54-7 (EC no) 265-157-1 (EC index no) 649-467-00-8 (REACH-no) 01-2119484627-25	>= 50	Not classified	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	(CAS No) 72623-87-1 (EC no) 276-738-4 (EC index no) 6494-483-00-5 (REACH-no) 01-2119474889-13	25 - 35	Not classified	Asp. Tox. 1, H304
mineral oil		5 - 10	Not classified	Asp. Tox. 1, H304
Methacrylate copolymer		1 - 2,5	Xi; R36	Eye Irrit. 2, H319
Alkoxy sulfolane		1 - 2,5	N; R51/53	Aquatic Chronic 2, H411

Full text of R- and H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Seek medical attention if ill effect develops.
First-aid measures after inhalation	: Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical advice. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.
First-aid measures after ingestion	: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/injuries after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Symptoms/injuries after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/injuries after ingestion	: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
Symptoms/injuries upon intravenous administration	: Unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> ), dry chemical powder, foam. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustion generates : CO, CO <sub>2</sub> , POx, NOx, SOx, H <sub>2</sub> S. Metal oxides.
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.

#### 5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.

# EuroI ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.
Other information	: Prevent fire-fighting water from entering environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
------------------	--

##### 6.1.1. For non-emergency personnel

Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
----------------------	--

Emergency procedures	: Consider evacuation.
----------------------	------------------------

##### 6.1.2. For emergency responders

Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
----------------------	---

Emergency procedures	: No specific measures are necessary.
----------------------	---------------------------------------

#### 6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.
Other information	: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
Precautions for safe handling	: Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.
Hygiene measures	: Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep container tightly closed and in well ventilated place.
Storage conditions	: Store in original container.
Incompatible products	: Reacts vigorously with strong oxidizers and acids.
Maximum storage period	: 5 year
Storage temperature	: ≤ 40 °C.
Prohibitions on mixed storage	: Keep away from : oxidizing materials. strong acids.
Storage area	: Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

# Eurol ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Belgium	Limit value (mg/m³)	5 mg/m³
mineral oil		
EU	IOELV TWA (mg/m³)	5 mg/m³
Belgium	Limit value (mg/m³)	5 mg/m³
Belgium	Short time value (mg/m³)	10 mg/m³
Bulgaria	OEL TWA (mg/m³)	5 mg/m³
Czech Republic	Expoziční limity (PEL) (mg/m³)	5 mg/m³
Czech Republic	Expoziční limity (NPK-P) (mg/m³)	10 mg/m³
Finland	HTP-arvo (8h) (mg/m³)	5 mg/m³
Greece	OEL TWA (mg/m³)	5 mg/m³
Hungary	MK-érték	5 mg/m³
Ireland	OEL (8 hours ref) (mg/m³)	5 mg/m³
Latvia	OEL TWA (mg/m³)	5 mg/m³
Lithuania	IPRV (mg/m³)	1 mg/m³
Netherlands	Grenswaarde TGG 8H (mg/m³)	5 mg/m³
Poland	NDS (mg/m³)	5 mg/m³
Poland	NDSch (mg/m³)	10 mg/m³
Romania	OEL TWA (mg/m³)	5 mg/m³
Romania	OEL STEL (mg/m³)	10 mg/m³
Slovakia	NPHV (priemerná) (mg/m³)	5 mg/m³
Spain	VLA-ED (mg/m³)	5 mg/m³
Spain	VLA-EC (mg/m³)	10 mg/m³
Sweden	nivågränsvärde (NVG) (mg/m³)	1 mg/m³
Sweden	kortidsvärde (KTV) (mg/m³)	3 mg/m³
Norway	Gjennomsnittsverdier (AN) (mg/m³)	1 mg/m³
USA - ACGIH	ACGIH TWA (mg/m³)	5 mg/m³
USA - ACGIH	ACGIH STEL (mg/m³)	10 mg/m³

Exposure-value for oil mist : 10 mg/m³ (15 min.) or 5 mg/m³ (8 hours).

### 8.2. Exposure controls

Appropriate engineering controls	: Large quantities: Contain large spillage with sand or earth.
Personal protective equipment	: Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.
Materials for protective clothing	: PVC gloves. Neoprene or nitrile rubber gloves
Hand protection	: In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).
Eye protection	: Eye protection should only be necessary where liquid could be splashed or sprayed
Skin and body protection	: No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.
Respiratory protection	: Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.



Environmental exposure controls : See Heading 12. See Heading 6.

# Eurol ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Consumer exposure controls	: PVC gloves. Neoprene or nitrile rubber gloves.
Other information	: Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: liquid
Appearance	: Oily. liquid.
Colour	: Red.
Odour	: characteristic.
Odour threshold	: no data available
pH	: no data available
Relative evaporation rate (butylacetate=1)	: < 0,1
Melting point	: <= -40 °C.
Freezing point	: no data available
Boiling point	: > 280 °C.
Flash point	: 211 °C.
Auto-ignition temperature	: > 240 °C.
Decomposition temperature	: no data available
Flammability (solid, gas)	: no data available
Vapour Pressure 20°C	: < 0,1 hPa
Relative vapour density at 20 °C	: > 1 (air=1)
Relative density	: no data available
Density	: 0,840 - 0,850 kg/l
Solubility	: insoluble in water.
Log Pow	: > 3
Viscosity, kinematic	: 50 - 100 cSt
Viscosity, dynamic	: no data available
Explosive properties	: no data available
Oxidising properties	: no data available
Explosive limits	: 0,6 - 7 vol %

#### 9.2. Other information

VOC content	: 0 %
Other properties	: Gas/vapour heavier than air at 20°C.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under normal conditions of use.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

#### 10.4. Conditions to avoid

Moisture. Overheating.

#### 10.5. Incompatible materials

Strong oxidizing agents. strong acids.

#### 10.6. Hazardous decomposition products

No additional information available

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified (Based on available data, the classification criteria are not met)
----------------	---

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

# EuroI ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 5,53 mg/l

### mineral oil

LD50 dermal rat	> 5000 ml/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	> 2,18 mg/l/4h

### Alkoxy sulfolane

LD50 oral	> 5000 mg/kg
LD50 dermal rabbit	> 2000 ml/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

### EuroI ATF 6100

Viscosity, kinematic	50 - 100 mm <sup>2</sup> /s
----------------------	-----------------------------

Other information	: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely route of exposure: ingestion, skin and eye.
-------------------	---

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Ecology - water	: This product floats on water and may affect the oxygen-balance in the water.

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l

### Alkoxy sulfolane

LC50 fish 1	4,2 ml/l 96h
EC50 Daphnia 1	2,5 mg/l 48h
ErC50 (algae)	3,5 mg/l 72h

### 12.2. Persistence and degradability

#### EuroI ATF 6100

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

### 12.3. Bioaccumulative potential

#### EuroI ATF 6100

Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.

### 12.4. Mobility in soil

#### EuroI ATF 6100

Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.
----------------	--

### 12.5. Results of PBT and vPvB assessment

#### EuroI ATF 6100

PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	

### 12.6. Other adverse effects

No additional information available

# Eurol ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information	: Hazardous waste.
Ecology - waste materials	: Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW) code	: 13 02 06* - Synthetic engine, gear and lubricating oils

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

Not regulated for transport

#### 14.2. UN proper shipping name

Proper Shipping Name	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

#### 14.3. Transport hazard class(es)

**ADR**  
**IMDG**  
**IATA**  
**ADN**  
**RID**

Transport hazard class(es) (ADR) : Not applicable

Transport hazard class(es) (IMDG) : Not applicable

Transport hazard class(es) (IATA) : Not applicable

Transport hazard class(es) (ADN) : Not applicable

Transport hazard class(es) (RID) : Not applicable

#### 14.4. Packing group

Packing group (UN)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

#### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

#### 14.6. Special precautions for user

##### - Overland transport

no data available

##### - Transport by sea

no data available

# Eurol ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### - Air transport

no data available

### - Inland waterway transport

Not subject to ADN : No

### - Rail transport

Carriage prohibited (RID) : No

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

#### 15.1.2. National regulations

##### Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 4.)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : Distillates (petroleum) hydrotreated light naphthenic, Distillates (petroleum), hydrotreated heavy paraffinic are listed

SZW-lijst van mutagene stoffen : Distillates (petroleum) hydrotreated light naphthenic, Distillates (petroleum), hydrotreated heavy paraffinic are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

##### Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of R-, H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects
EUH208	Contains . May produce an allergic reaction
EUH210	Safety data sheet available on request
R36	Irritating to eyes
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
N	Dangerous for the environment
Xi	Irritant



# EuroI ATF 6100

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

---

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*