

TECHNICAL CHARACTERISTICS

SELENIA TURBO DIESEL 10W-40

PRODUCT CODE: 1091

APPLICATION

Synthetic based motor oil for Diesel cars equipped turbo-charged or multi-valve indirect or direct injection engines. Also ideal for aspirated diesel cars.

SPECIFICATIONS

SAE 10W-40, ACEA B3, API CF/SG, CCMC PD2, FIAT 9.55535-D2 CONTRACTUAL TECHNICAL REFERENCE N°F009.B99, VW 505.00, MIL-L-2104 D Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY @ 15°C	ASTM D 5931	g/cm3	0,878
VISCOSITY @ 100°C	ASTM D 445	cSt	14,8
VISCOSITY INDEX	ASTM D 2270	--	155
FLASH POINT CI. O. C.	ASTM D 92	°C	210
T.B.N.	ASTM D 2896	mg KOH/g	7,4
POUR POINT	ASTM D 97	°C	<-27
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

11/2010