

# SELENIA WR 5W-40 Cod. 1092


## DESCRIPTION

Highly selected synthetic based oil for direct injection engines, both aspirated and turbo-charged. It is developed to respond to all requirements of the latest generation diesel engines (common-rail), where the revolutions per minute and the specific power of the engine are enhanced. As a result of the particular additives, it also ensures complete protection of the engine. Recommended by Fiat / Lancia / Alfa Romeo for Multijet engines.

## CHARACTERISTICS

SELENIA WR is formulated with a correct balance of the detergent additives and dispersants that help to reduce and control the formation of deposits, combustion residue and carbon deposits guaranteeing the optimal operation of the engine.

- | The advanced viscosity grade 5W-40 ensures the use of the product in more extreme temperatures:  
SAE 5W allows excellent lubrication and engine start up to -30°C;  
SAE 40 guarantees the lubrication film with external temperatures up to +40°C.
- | Minor fuel consumption and reduced emissions
- | Thermal stability preventing oxidation;
- | Wear reduction;
- | Special formula "air release" to grant idraulic tappets control;
- | Particularly suited to JTD or common rail engines where the revolutions per minute and the specific power of the engines are enhanced.



## ADVICE ON USE

Replacement should be as indicated by Fiat.

## RECOMMENDED BY

Fiat, Lancia, Alfa Romeo for Multijet engines and cold climates.

## TECHNICAL DATA

SAE 5W-40, API CF, ACEA B3/B4,  
FIAT 9.55535-N2 CONTRACTUAL TECHNICAL REFERENCE N°F515.D06,  
GM-LL-B-025, VW 502.00, VW 505.00,  
MB 229.3 Performance