# SAFETY DATA SHEET



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Castrol Syntrax Long Life 75W-140

Product code 467189-DE01
SDS no. 467189
Product type Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Automotive gear lubricant

mixture For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

1.3 Details of the supplier of the safety data sheet

**Supplier** BP Europa SE

Überseeallee 1 D-20457 Hamburg

Germany

Customer Service Center / Environmental Protection / Product Safety: +49 (0)40 639-52222

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

**EMERGENCY** Carechem: +44 (0) 1235 239 670 (24/7)

**TELEPHONE NUMBER** 

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word No signal word.

**Hazard statements** No known significant effects or critical hazards.

**Precautionary statements** 

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Supplemental label Contains Long chain alkyl amine. May produce an allergic reaction.

elements

**Special packaging requirements** 

Containers to be fitted with child-resistant fastenings

Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Other hazards which do Defatting to the skin.

the hazard classification of this product.

Product nameCastrol Syntrax Long Life 75W-140Product code467189-DE01Page: 1/10Version 4Date of issue 24 October 2016FormatGermanyLanguageENGLISH

# **SECTION 3: Composition/information on ingredients**

Substance/mixture Mix

Synthetic base stock. Proprietary performance additives.

Product/ingredient Identifiers % Regulation (EC) No. Type name 1272/2008 [CLP]

©ec-1-ene, trimers, hydrogenated REACH #: 01-2119493949-12 ≥25 - ≤50 Asp. Tox. 1, H304 [1]

EC: 500-393-3 CAS: 157707-86-3

Tricresyl phosphate Proprietary <3 Repr. 2, H361fd (Fertility and [1]

Unborn child)

Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410

(M=1)

See Section 16 for the full text of the H statements declared above.

#### **Type**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids

should be held away from the eyeball to ensure thorough rinsing. Check for and remove any

contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before

reuse. Get medical attention if irritation develops.

**Inhalation** If inhaled, remove to fresh air. Get medical attention if symptoms appear.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if

symptoms occur.

**Protection of first-aiders**No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing

media

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet.

# 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** 

Combustion products may include the following:

products

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

# 5.3 Advice for firefighters

Special precautions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Product nameCastrol Syntrax Long Life 75W-140Product code467189-DE01Page: 2/10

Version 4 Date of issue 24 October 2016 Format Germany Language ENGLISH

# **SECTION 5: Firefighting measures**

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

**Protective measures** Put on appropriate personal protective equipment. Avoid contact of spilt material and runoff

with soil and surface waterways.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers.

Not suitable Prolonged exposure to elevated temperature.

**Germany - Storage code** 10

7.3 Specific end use(s)

Recommendations See section 1.2 and Exposure scenarios in annex, if applicable.

# SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

**Occupational exposure limits** 

No exposure limit value known

Product name Castrol Syntrax Long Life 75W-140 Product code 467189-DE01 Page: 3/10 Language ENGLISH Version 4 Date of issue 24 October 2016 Format Germany (Germany)

# **SECTION 8: Exposure controls/personal protection**

# Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **Derived No Effect Level**

No DNELs/DMELs available.

#### **Predicted No Effect Concentration**

No PNECs available

#### 8.2 Exposure controls

# Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

#### **Individual protection measures**

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Respiratory protection

rease of insufficient ventilation, wear suitable respiratory equipment.

For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3). Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

# Eye/face protection Skin protection Hand protection

Safety glasses with side shields.

#### **General Information:**

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

# Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Product nameCastrol Syntrax Long Life 75W-140Product code467189-DE01Page: 4/10Version 4Date of issue 24 October 2016FormatGermanyLanguageENGLISH(Germany)

# **SECTION 8: Exposure controls/personal protection**

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

#### **Glove Thickness:**

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

#### Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

**Refer to standards:** 

Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state
Colour
Not available.

Odour
Not available.

Odour threshold
Not available.

PH
Not available.

Melting point/freezing point
Not available.

Initial boiling point and boiling
range
Liquid.
Not available.

Not available.
Not available.

Product nameCastrol Syntrax Long Life 75W-140Product code467189-DE01Page: 5/10Version 4Date of issue 24 October 2016FormatGermanyLanguageENGLISH

# **SECTION 9: Physical and chemical properties**

Pour point -54 °C

Flash point Open cup: 234°C (453.2°F) [Cleveland.]

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or Not available.

explosive limits

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

**Density** 869.8 kg/m³ (0.87 g/cm³) at 15°C

Solubility(ies) insoluble in water.

Partition coefficient: n-octanol/ Not available.

water

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Kinematic: 182 mm<sup>2</sup>/s (182 cSt) at 40°C

Kinematic: 25 mm<sup>2</sup>/s (25 cSt) at 100°C

**Explosive properties**Not available. **Oxidising properties**Not available.

#### 9.2 Other information

No additional information.

# SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible

materials for additional information.

**10.2 Chemical stability** The product is stable.

10.3 Possibility of Londer normal conditions of storage and use, hazardous reactions will not occur.
 Londer normal conditions of storage and use, hazardous polymerisation will not occur.

**10.4 Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

**10.5 Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.

**10.6 Hazardous**Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### **Acute toxicity estimates**

Route	ATE value
Dermal	90702.9 mg/kg
Inhalation (vapours)	151.2 mg/l

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

# Potential acute health effects

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low vapour

pressure.

**Ingestion** No known significant effects or critical hazards.

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal

decomposition products occurs.

Ingestion No specific data.

Product nameCastrol Syntrax Long Life 75W-140Product code467189-DE01Page: 6/10Version 4Date of issue 24 October 2016FormatGermanyLanguageENGLISH

# **SECTION 11: Toxicological information**

**Skin contact** Adverse symptoms may include the following:

irritation dryness cracking

Eye contact No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the

respiratory tract.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.

**Skin contact** Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

#### Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Environmental hazards Not classified as dangerous

Product not classified for environmental effects. Based on data available for this or related

materials.

#### 12.2 Persistence and degradability

Not expected to be rapidly degradable.

#### 12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

#### 12.4 Mobility in soil

Soil/water partition Not available.

coefficient (Koc)

**Mobility** Spillages may penetrate the soil causing ground water contamination.

#### 12.5 Results of PBT and vPvB assessment

PBT Not applicable.

vPvB Not applicable.

#### 12.6 Other adverse effects

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen

transfer could also be impaired.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

### **Product**

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes.

European waste catalogue (EWC)

Waste code	Waste designation	
13 02 08*	other engine, gear and lubricating oils	

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

#### **Packaging**

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Product nameCastrol Syntrax Long Life 75W-140Product code467189-DE01Page: 7/10Version 4Date of issue 24 October 2016Format GermanyLanguageENGLISH

# **SECTION 13: Disposal considerations**

**Special precautions** 

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user

Not available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not available.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

**Other regulations** 

**REACH Status** 

The company, as identified in Section 1, sells this product in the EU in compliance with the

current requirements of REACH.

**United States inventory** 

(TSCA 8b)

All components are listed or exempted.

**Australia inventory (AICS)** 

s) A

All components are listed or exempted.

Canada inventory
China inventory (IECSC)

All components are listed or exempted. All components are listed or exempted.

Japan inventory (ENCS) Korea inventory (KECI) All components are listed or exempted.

All components are listed or exempted.

Philippines inventory (PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory Not determined.

(TCSI)

**National regulations** 

Hazard class for water 2 Appendix No. 4 (classified according VwVwS)

Product nameCastrol Syntrax Long Life 75W-140Product code467189-DE01Page: 8/10Version 4Date of issue 24 October 2016FormatGermanyLanguageENGLISH(Germany)

# **SECTION 15: Regulatory information**

#### 15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

#### **SECTION 16: Other information**

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SADT = Self-Accelerating Decomposition Temperature

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Varies = may contain one or more of the following 101316-69-2 / RRN 01-2119486948-13, 101316-70-5, 101316-71-6, 101316-72-7 / RRN 01-2119489969-06, 64741-88-4 / RRN

01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64741-97-5 / RRN 01-2119480374-36, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN

01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN

01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-64-9, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42,

72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13, 74869-22-0 / RRN 01-2119495601-36, 90669-74-2 / RRN

01-2119970171-43

Full text of abbreviated H statements

**H**304 May be fatal if swallowed and enters airways.

H361fd (Fertility and Unborn Suspected of damaging fertility. Suspected of damaging the child) unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**Full text of classifications** Aquatic Acute 1, H400 [CLP/GHS]

ACUTE AQUATIC HAZARD - Category 1 Aquatic Chronic 1, H410 LONG-TERM AQUATIC HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Asp. Tox. 1, H304 Repr. 2, H361fd (Fertility TOXIC TO REPRODUCTION (Fertility and Unborn child) -

and Unborn child) Category 2

**History** 

Date of issue/ Date of

revision

24/10/2016.

Product name Castrol Syntrax Long Life 75W-140 Product code 467189-DE01 Page: 9/10 Language ENGLISH Version 4 Date of issue 24 October 2016 Format Germany (Germany)

# **SECTION 16: Other information**

Date of previous issue 29/04/2015.

Prepared by Product Stewardship

Indicates information that has changed from previously issued version.

#### **Notice to reader**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameCastrol Syntrax Long Life 75W-140Product code467189-DE01Page: 10/10Version 4Date of issue 24 October 2016FormatGermanyLanguageENGLISH