



your local global brand

Ultrasynth GMX 5W-30

Synthetic Energy Conserving Motor Oil

Product Description

Gulf Ultrasynth GMX 5W-30 is the advanced synthetic energy conserving motor oil specially developed for the most modern high output gasoline and turbocharged engines in passenger cars, sport utility vehicles and light-duty trucks, operating on ethanol-containing fuels up to E85. It is formulated to help improve & retain fuel economy and protect vehicle emission system & turbocharger components.

Gulf Ultrasynth GMX 5W-30 is based on exceptional quality synthetic base oil in combination with a special selected additive package to reach to following properties:

- Improving sludge protection, piston cleanliness, turbo-charger protection, seal compatibility, wear protection over other API SN/GF5 oils.
- Special friction modifiers used in this Energy conserving oil help improving & retaining fuel economy.
- Offers excellent lubrication at low temperatures and protect engine at high temperatures.
- Superior volatility characteristics reduce oil consumption and hydro-carbon pollution (VOCs).
- Advanced additive chemistry helps in emission system durability.
- Compatible with ethanol-containing fuels up to E85.

Gulf Ultrasynth GMX 5W-30 exceeds the following performance criteria

Approved API SN (Resource Conserving) ILSAC GF-5

Exceeds GM Dexron 1™

Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m ³	ASTM D4052	852
Kin. Viscosity @40°C	mm ² /s	ASTM D445	63.4
Kin. Viscosity @100°C	mm ² /s	ASTM D445	11.1
Viscosity index		ASTM D2270	168
Viscosity CCS@-30°C, max	cP	ASTM D2983	6600
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	7.9
Sulphated Ash	%Wt	ASTM D874	0.93

Product Code: 1228	Date Issued: 30-08-2013	Date Reviewed:	Revision:
---------------------------	-------------------------	----------------	-----------