



your local global brand

Gulf Multi G 15W-40

Passenger Car Motor Oil

Product Description:

Gulf Multi G 15W-40 is a passenger car motor oil designed for older gasoline powered passenger cars and naturally aspirated diesel engines of light duty vehicles. **Gulf Multi G 15W-40** is blended using good quality base oils and performance additives to ensure better engine protection.

Gulf Multi G 15W-40 has good thermo-oxidative stability that minimises deposits & sludge build-up, effective rust inhibitors retard formation of rust in critical engine parts, antiwear technology minimises engine wear & reduces maintenance costs and good stay-in-grade performance ensures reliable lubrication even at higher load & operating temperatures.

Gulf Multi G 15W-40 is recommended for use in passenger cars, light trucks and vans with naturally aspirated gasoline engines or light-duty diesel engines, where API SF/CD quality oil is required and is suitable for year-round use under wide temperature conditions and ensures trouble free operation.

Meets the specifications of: API SF/CD

<u>Properties:</u>	<u>Test Methods:</u>	<u>Typical Values:</u>
SAE Viscosity Grade	SAE J300	15W-40
Density @ 15°C	ASTM D4052	883 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D445	105 mm ² /s (cSt)
Kinematic Viscosity @ 100°C	ASTM D445	14.2 mm ² /s (cSt)
Low-Temperature Cranking Viscosity @ -20°C	ASTM D5293	<7000 mPa.s (cP)
Viscosity Index	ASTM D2270	>135
Flash Point	ASTM D92	220°C
Pour Point	ASTM D97	<-27°C
Total Base Number	ASTM D2896	5.2 mgKOH/g
Sulphated Ash	ASTM D874	0.67 wt %

Product Code: 1330	Date Issued: 15/06/2012	Date Superseded: 28/11/2011	Revision nr: 04
--------------------	-------------------------	-----------------------------	-----------------