

TECHNICAL CHARACTERISTICS

TUTELA G/R

PRODUCT CODE: 1442

APPLICATION

Special fluids for elettrohydraulic steering systems, central self-levelling unit,hydraulic actuators for capotte.

SPECIFICATIONS

ISO VG 22, FIAT 9.55550-AG3 CONTRACTUAL TECHNICAL REF. N°F428.H04, ZF TE-ML 02K,
IVECO 18-1807 CLASSE APU,CONTRACTUAL TECHNICAL REF. N°I428.I07, MS-11655,
MB 345.0 Performance, MAN M3289

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	BRIGHT & CLEAR
COLOUR	--	--	GREEN
DENSITY 15°C	ASTM D 4052	g/cm ³	0,830
VISCOSITY @ 40°C	ASTM D 445	cSt	18,7
VISCOSITY @ 100°C	ASTM D 445	cSt	6,0
VISCOSITY INDEX	ASTM D 2270	--	313
VISCOSITY @ -40°C	ASTM D 2983	cPs	1100
FLASH POINT Cl. O. C.	ASTM D 92	°C	157
POUR POINT	ASTM D 97	°C	-57

All technical data is provided for reference only.