

# TUTELA TRANSMISSION W90 M-DA Cod. 1452

## DESCRIPTION

Axle fluid for any vehicle applications. It is suitable for differentials with hypoid gears and steering boxes, where lubrication with Extreme Pressure (E.P.) characteristics is required.

## CHARACTERISTICS

- | Excellent E.P. properties in order to allow optimal protection even in extreme conditions (starting, acceleration etc.) and of high load with low revs.
- | Excellent anti-wear characteristics for more durable transmission components (gears, bearings, shafts, selectors, etc).
- | High anti-foaming and demulsifying characteristics in order to guarantee constant lubrication and maximum heat removal.
- | High viscosity index in order to optimise the fluency in every operating temperature condition.



## ADVICE ON USE

TUTELA W90 M-DA is available in SAE 80W-90 grade for all year use.

Replacement as indicated by the manufacturer.

## RECOMMENDED BY

Fiat Group Automobiles, Iveco,

## TECHNICAL DATA

SAE 80W-90, API GL 5,  
IVECO 18-1805 CLASSE RAM1, CONTRACTUAL TECHNICAL REF. N°I009.G87,  
FIAT 9.55550-DA2, ZF TE-ML 16B, ZF TE-ML 17B,  
ZF TE-ML 19B, ZF TE-ML 21A,  
MIL-L-2105 D Performance