



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Date of the previous version: 2016-04-26

Revision Date: 2016-12-29

Version 4.01

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	QUARTZ DIESEL 7000 10W-40
Number	717
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'île 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71
-----------------	--

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670
 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59
 In France - Poison centers:
 ANGERS : 02 41 48 21 21
 BORDEAUX : 05 56 96 40 80
 LILLE : 08 00 59 59 59
 LYON : 04 72 11 69 11
 MARSEILLE : 04 91 75 25 25
 NANCY : 03 83 22 50 50
 PARIS : 01 40 05 48 48
 STRASBOURG : 03 88 37 37 37
 TOULOUSE : 05 61 77 74 47

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture**REGULATION (EC) No 1272/2008**

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008

2.2. Label elements

Labelled according to REGULATION (EC) No 1272/2008

Hazard Statements

None

Precautionary Statements

None***

Supplemental Hazard Statements

EUH210 - Safety data sheet available on request***

EUH208 - Contains Calcium long chain alkaryl sulfonate. May produce an allergic reaction

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture**Hazardous ingredients**

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	265-169-7***	01-2119471299-27	64742-65-0	50-<60	Asp. Tox. 1 (H304)
Distillates (petroleum), hydrotreated heavy paraffinic	265-157-1***	01-2119484627-25	64742-54-7	20-<30	Asp. Tox. 1 (H304)
Polyolefin polyamine succinimide, polyol	-	no data available	147880-09-9	2.5-<5	Aquatic Chronic 4 (H413)
Zinc alkyl dithiophosphate	272-028-3***	01-2119657973-23	68649-42-3	1-<2.5	Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)
Calcium long chain alkaryl sulfonate	-	-	722503-69-7	1-<2.5	Aquatic Chronic 4 (H413)
Calcium long chain alkaryl sulfonate***	-	-	722503-68-6	0.1-<1	Aquatic Chronic 4 (H413) Skin Sens.1 (H317)

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Not classified. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required.
Skin contact	Not classified. May produce an allergic reaction.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician	Treat symptomatically.
---------------------------	------------------------

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media	Carbon dioxide (CO ₂). ABC powder. Foam. Water spray or fog.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may
-----------------------	--

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid

Strong oxidizing agents.

7.3. Specific end uses**Specific use(s)**

No information available.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION8.1. Control parameters**Exposure limits**

Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

Legend

See section 16

DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0				5.4 mg/m ³ /8h (aerosol - inhalation)
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7				5.4 mg/m ³ /8h (aerosol - inhalation)

DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0				1.2 mg/m ³ /24h (aerosol - inhalation)
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7				1.2 mg/m ³ /24h (aerosol - inhalation)

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

8.2. Exposure controls**Occupational Exposure Controls****Engineering Measures**

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal Protective Equipment**General Information**

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Eye Protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.

Hand Protection

Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency.

Environmental exposure controls**General Information**

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES9.1. Information on basic physical and chemical properties

Appearance	limpid
Color	yellow
Physical State @20°C	liquid
Odor	Characteristic
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		Not applicable	
Boiling point/boiling range		No information available	
Flash point	234 °C 453 °F		Open cup Open cup

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper ***	***	No information available***	***
Lower ***	***	No information available***	***
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.862 - 0.872	@ 15 °C	
Density	862 - 872 kg/m ³	@ 15 °C	
Water solubility		No information available	
Solubility in other solvents		No information available	
logPow ***		No information available***	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	100.9 mm ² /s	@ 40 °C	ISO 3104
	14.6 - 15.4 mm ² /s	@ 100 °C	ISO 3104
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	No information available		

9.2. Other information

Freezing Point No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information No information available.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes

Version EU

SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

and soot.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact	. Not classified. May produce an allergic reaction.
Eye contact	. Not classified. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required.
Inhalation	. Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
ATEmix (oral)	19,625.00 mg/kg
ATEmix (dermal)	19,036.00 mg/kg
ATEmix (inhalation-dust/mist)	20.60 mg/l
ATEmix (inhalation-vapor)	1,476.50 mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5.53 mg/l (aerosol) (rat - OECD 403)
Distillates (petroleum), hydrotreated heavy paraffinic	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Zinc alkyldithiophosphate	LD50 2900 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	

Sensitization

Sensitization Not classified as a sensitizer. Contains sensitizer(s). May produce an allergic reaction.

Specific effects

Carcinogenicity This product is not classified carcinogenic. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Mutagenicity This product is not classified as mutagenic.

Reproductive toxicity This product does not present any known or suspected reproductive hazards.

Repeated Dose Toxicity

Subchronic toxicity No information available.

Target Organ Effects (STOT)

Other information

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated

SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0		EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Zinc alkylidithiophosphate 68649-42-3	EC50 (72h) 2.2 mg/l	EC50 (48h) 1.2 mg/l (Daphnia magna)	LC50 (96h) 4.5 mg/l	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Zinc alkylidithiophosphate 68649-42-3	NOEC 1.0 mg/l	NOEC (21d) 0.4 mg/l (Daphnia magna)	NOEC(28d) 1.8 mg/l	

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information

No information available.

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

12.3. Bioaccumulative potential**Product Information** No information available.**logPow** *** No information available*****Component Information**

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic - 64742-54-7	-
Zinc alkyldithiophosphate - 68649-42-3	0.56

12.4. Mobility in soil**Soil** Given its physical and chemical characteristics, the product generally shows low soil mobility.**Air** Loss by evaporation is limited.**Water** Insoluble. The product spreads on the surface of the water.12.5. Results of PBT and vPvB assessment**PBT and vPvB assessment** No information available.12.6. Other adverse effects**General Information** No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

EWC Waste Disposal No. The following Waste Codes are only suggestions: 13 02 05. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

ADR/RID Not regulated

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

IMDG/IMO Not regulatedICAO/IATA Not regulatedADN Not regulated**Section 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

European Union

Further information

No information available

15.2. Chemical Safety Assessment**Chemical Safety Assessment** No information available**Section 16: OTHER INFORMATION****Full text of H-Statements referred to under sections 2 and 3**

H304 - May be fatal if swallowed and enters airways
 H317 - May cause an allergic skin reaction
 H318 - Causes serious eye damage
 H411 - Toxic to aquatic life with long lasting effects
 H413 - May cause long lasting harmful effects to aquatic life

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists
 bw = body weight
 bw/day = body weight/day
 EC x = Effect Concentration associated with x% response
 GLP = Good Laboratory Practice
 IARC = International Agency for Research of Cancer
 LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals
 LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals
 LL = Lethal Loading
 NIOSH = National Institute of Occupational Safety and Health
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 NOEL = No Observed Effect Level
 OECD = Organization for Economic Co-operation and Development

Version EU



SDS # : 31033

QUARTZ DIESEL 7000 10W-40

Revision Date: 2016-12-29

Version 4.01

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water

or = occasional release

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

PEL: Permissible exposure limit

REL: Recommended exposure limit

TLV: Threshold Limit Values

+ Sensitizer

** Hazard Designation

M: Mutagen

* Skin designation

C: Carcinogen

R: Toxic to reproduction

Revision Date: 2016-12-29**Revision Note** *** Indicates updated section.**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet