Technical Data Sheet

Revised: 2015/09/04(version 1.0)

PETRONAS Syntium 3000 FR 5W-30



APPLICATIONS

Suitable for all types of passenger cars, such as Ford & Renault engines. It is suitable for both gasoline and diesel engines and latest high performance cars fitted with fuel injections, multi-valves, turbochargers or superchargers operating under most severe conditions

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

SPECIFICATIONS & APPROVALS*

Meets or Exceeds the requirements of:	API SN, ACEA A5/B5	
Has the following builder approvals:	Ford WSS-M2C913-C, 913-D	
	Renault RN0700	

^{*} All technical data is provided for reference only.

 Outstanding High Temperature Oxidation Control, delivering lubrication stability and prevents car breakdowns.

FEATURES & BENEFITS

- Withstanding high temperature lubricants evaporation loss to stop premature thermal degradation to help preventing engine failure from wear & tear.
- Superior fuel economy, as it exceeds European standards ACEA A5/B5.
- Superior engine depositis and wear reduction, hence delivering maximized engine responsiveness.
- Instant start-up lubrication

TYPICAL PHYSICAL DATA**

Parameters	Method	Unit	Typical Value
Appearance	-	-	B&C
Density 15°C	ASTM D 4052	g/cm²	0.852
Viscosity @100°C	ASTM D 445	cSt	10.0
Viscosity Index	ASTM D 2270	-	166
Flash Point CI. O. C	ASTM D 92	°C	>220
TBN	ASTM D 2896	mg KOH/g	10.3
Pour Point	ASTM D 97	°C	<-37
Foam @24°C	ASTM D 892	cc/s	Traces/0

^{**} These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

OIL TYPE

Synthetic

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refers to product SDS or contact us at: www.plipetronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contains herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 1807