



RED LINE 5W20 MOTOR OIL



- Recommended for Chrysler, Ford WSS-M2C945-A, Acura/Honda, Mazda and Scion
- Thicker oil film at operating temperature than a petroleum 5W30 or 10W30

RECOMMENDED FOR:

ILSAC GF-5
API SN/SM/SL/CF
ACEA A5/B5

AC Delco
 88863951
 88863952

Ford
 WSS-M2C153-H
 WSS-M2C925-A
 WSS-M2C945-A
 XO-5W20-5QSP
 XO-5W20-QFS

GM
 19264714
 19264715
 19264716
 9986202-2000
 dexos1®

dexos is a registered trademark owned by General Motors Corp.

Mopar
 04761851PA
 04761872MB
 04761872PB
 05166240PA
 68079549MB
 68169968PA
 MS-6395L, M

Honda/Acura
 08798-9032
 08798-9038

Mazda
 0000-77-5W20-QT

Toyota
 00279-1QT20-01

TYPICAL PROPERTIES:

ACEA Service Class	A5 B5
API Service Class	SN/SM/SL/CF
SAE Viscosity Grade (Motor Oil)	5W20
Vis @ 100°C, cSt	9.0
Vis @ 40°C, cSt	53
Viscosity Index	147
CCS Viscosity, Poise, @ °C	60@-30
Pour Point, °C	-45
Pour Point, °F	-49
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	8
HTHS Vis, cP @150°C, ASTM D4741	3.0

PACKAGE SIZES:

- 15204 - 5W20 Motor Oil - quart
- 15205 - 5W20 Motor Oil - gallon
- 15206 - 5W20 Motor Oil - 5 gallon
- 15208 - 5W20 Motor Oil - 55 gallon

ABOUT RED LINE MOTOR OIL

- Full synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM