



Quality is in our nature

Eurol Ultrance VA 0W-30

Fuel economy, fully synthetic oil for diesel and gasoline engines

Description

Eurol Ultrance VA 0W-30 is a long-life, 'full saps' technology, fully synthetic based oil formulation. Eurol Ultrance VA 0W-30 has a universal applicability in certain modern engines Euro-4, Euro-5 and Euro-6, diesel or gasoline, naturally aspirated or turbocharged, indirect or direct injection, requiring a SAE 0W-30 with ACEA A5/B5 and API SL specifications.

Eurol Ultrance VA 0W-30 enables the engine to perform under all operating conditions (motorway and urban traffic) due to its special additive package.

Eurol Ultrance VA 0W-30 is providing excellent performance in piston cleanliness, in reducing the formation of sludge and in keeping the turbocharger clean. Also improved fuel economy (min 5% in comparison with a mineral SAE 15W-40) and low emission reduction for powerful engines can be obtained with this product. Because of the unique formulation, the oil has a low evaporation tendency, minimizing oil consumption.

Eurol Ultrance VA 0W-30 offers low temperature properties for cold weather starting allowing easy starts and optimal lubrication of the engine.

Eurol Ultrance VA 0W-30 is suitable for long oil change intervals and high engine loads according to the manufacturer's instructions.

Eurol Ultrance VA 0W-30 is recommended for the recent engines (B5, B6, B8, D5, D82 and D87 from Volvo) powered with turbo diesel or gasoline engines requiring fuel economy lubricants (ACEA A1/B1 or ACEA A5/B5, e.g. Land Rover TD5 and 3.2 gasoline, Honda 1.8L and 2.0L gasoline engines). Eurol Ultrance VA 0W-30 is also recommended for the 5-cylinder gasoline and diesel engines requiring the Volvo VCC 95200377 specification.

Specifications

Approved

Volvo VCC 95200377

Performance level

API SL

ACEA A5/B5

Recommended for use

API CF

ACEA A1/B1

Physical properties

Colour	Brown	
Density at 20°C	0.842 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	53.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	10.2 cSt	ASTM D 445
Viscosity Index	181	ASTM D 2270
Viscosity, dynamic (CCS)	5740 cP	ASTM D 2602
HTHS	3 cP	CEC CL 23
Base number	9.8 mg KOH/g	ASTM D 2896
Sulphated ash	1.1 wt%	ASTM D 874
Flash point	200 °C	ASTM D 93
Pour point	-48 °C	ASTM D 97

Available in 1L, 5L

E100158

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com