



PENNZOIL ULTRA[™] 0W-40 FULL SYNTHETIC MOTOR OIL

Technical Data Sheet

PRODUCT DESCRIPTION

PENNZOIL ULTRA[™] FULL SYNTHETIC MOTOR OIL with Hyper Cleansing Technology[™], from the maker of the leading motor oil in America, is an advanced proprietary synthetic formula designed to exceed the toughest car manufacturer standards and engineered to keep your engine closer to factory clean. Because at Pennzoil we know, a cleaner engine is better protected, more efficient and delivers optimum performance.

PENNZOIL ULTRA[™] FULL SYNTHETIC MOTOR OIL is specially formulated for consumers who are committed to buying a synthetic lubricant, and who want nothing but our best motor oil.

APPLICATION

PENNZOIL ULTRA[™] FULL SYNTHETIC MOTOR OIL with Hyper Cleansing Technology[™] is compatible with all engine sealing materials, other synthetic oils and all conventional oils and is suitable for all cars, SUV's, light vans and trucks, gasoline and turbocharged engines, under all driving conditions where an API SN, SAE 0W-40 oil may be recommended. Not for use in Porsche, Mercedes-Benz, BMW and other European engines.

Pennzoil Ultra[™] is specifically formulated for the needs of Chrysler SRT engines where Chrysler MS-12633 oil is required. It may also be used in SRT engines originally recommending Chrysler MS-10725 oil.

FEATURES

- Hyper Cleansing Technology[™]
- Low Volatility Oil

BENEFITS

- Seeks out and dissolves contaminants safely into the oil before they form deposits in the engine.
- Helps to prevent the build-up of sludge, damaging deposits, corrosion and engine wear.
- Helps clean-up engines by gently lifting sludge deposits off engine surfaces and dissolving them safely into the oil.
- Provides oil stability and endurance under extreme conditions (heat, load and speed) for protection against viscosity and thermal breakdown
- Provides proven protection for critical engine parts.
- Helps protect emissions systems.

SPECIFICATIONS & APPROVALS

- API SN, SM, SL, SJ
- Chrysler MS-12633 approved

HEALTH & SAFETY

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Pennzoil representative.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

July 2012 001E5786



**TYPICAL PHYSICAL AND CHEMICAL PROPERTIES
PENNZOIL ULTRA™ FULL SYNTHETIC MOTOR OIL**

Viscosity Grade (SAE J300)		0W-40
API Service		SN
TEST	METHOD	
Viscosity @ 100°C, cSt	ASTM D-445	13.7
Pour Point, °C	ASTM D-97	-45
MRV viscosity, cP (°C)	ASTD D-4684	22,500 (-40)
CCS Viscosity, cP (°C)	ASTM D-5293	5,700 (-35)

These characteristics are typical. While future production will conform to Pennzoil® specifications, variations in these characteristics may occur. The information contained herein is subject to change without notification.