

Fully Synthetic

Kixx ATF Multi

Top Performance Multi-vehicle Automatic Transmission Fluid

JASO 1A, GM DEXRON®-III, TOYOTA T-IV,
HYUNDAI SP-III/SP-IV

DESCRIPTION

Kixx ATF Multi is a high-performance, high-quality multi-vehicle fluid for automatic transmissions. (Applicable for Slip controlled lock-up clutch) It is a specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications requiring SP-II, SP-III, DEXRON® III, MERCON®, Allison C-4, Toyota T-III and IV. In addition, it meets the requirements of European OEM's like ZF-TE-ML-11A/B, Volvo CE 97340, and MB, VW, BMW 4, 5 and 6-speed automatic transmission specifications. Kixx ATF Multi is a special blend of high quality base stocks with an advanced additives system for use as a Service-Fill.

PERFORMANCE STANDARDS

Auto Maker	Specification	Auto Maker	Specification
VW / Audi	G 052 162 (ZF Lifeguardfluid 5)	Hyundai / Kia	Dex-II, SP-II
	G 055 025 A2 (JWS 3309)		JWS 3314, NWS 9638
	G 052 990		SP-III, SP-IV, SP-IV RR
	ZF 5HP 18FL/19FL/24A/30		ATF RED 1, RED 1K
Mercedes Benz	TL 521 62	Jaguar	ATF 3403 JLM20238
	MB 236.1, 236.2, 236.3		ATF 3403-M115
	MB 236.5, 236.6, 236.7		ATF LT71141, ZF 5HP 24
	MB 236.8, 236.9	JASO	M315-2013 1A
BMW	7045E, ETL-8072B		M315-2013 2A
	JWS 3309 (T-IV)	Mazda	ATF 3317
	LT71141 (ZF 5 HP 18FL/19FL/24A/30)		ATF D-II, F-1, FZ
			ATF M-III, M-V, N-1, S-1
Ford	FNR5	Mitsubishi	Diaqueen ATF PA
	WSS M2C138CJ, M2C166H		Diaqueen J2, J3, SK
	WSS M2C 922A1, 924A		Diaqueen SP-II, SP-III, SP-IV
	MERCON®	Nissan	Matic Fluid C, D, J
Fuso	ATF-A4		Matic Fluid K, S
	ATF-II	Porsche	ATF 3403-M115
	ATF-SP III		T-IV (JWS 3309)
GM	DEXRON®-II, IID, IIE		ZF 5HP 19FL, 5HP 20, LT71141
	DEXRON®-III, IIIG, IIIG	Subaru	ATF, ATF 5AT, ATF HP
	TASA		ATF 2326, ATF 2384K
	GM9986195(Aisin AW, JWS 3309)		ATF 3314, ATF 3317
Honda	ATF Ultra II		JWS 3309
	ATF-Z1 (except in CVTs)	Toyota	ATF D-II, D-III, T-III, T-IV (JWS 3309)
	DW-1		ATF WS (JWS 3324)
			all 3 & 4 speed transmission
Chrysler / Dodge	ATF+, +2	ZF	TE-ML 09A, 11A, 11B
	ATF +3 (MS 7176E), +4 (MS 9602)		3403, M115, LA 2634
	JWS 3309 (T-IV)	Shell	7045-E, 8072B, N402
Isuzu	Besco ATF-II		
	Besco ATF-III		
JEEP	ATF+3, +4		

CUSTOMER BENEFITS

- Anti shudder protection.
- Oxidation and thermal stability
- Provides high foam stability.
- Provides good start operation in cold climates thanks to its excellent low-temperature fluidity.
- Provides more stable friction property.
- Use for most vehicles

KEY PROPERTIES

Density, kg/L @15°C	0.845
Kinematic Viscosity, mm ² /s @ 40°C	33.8
Kinematic Viscosity, mm ² /s @ 100°C	7
Pour Point °C	-45
Flash Point °C	220
Brookfield Viscosity, cP @-20°C	860
Brookfield Viscosity, cP @-40°C	12,730
Package (Liters)	1,4,4T,20,200


UNIQUE FEATURES

High Quality Multi-Vehicle Fluid for Automatic Transmissions

Specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications

- Hyundai/Kia/Mitsubishi SP-II, SP-III
- GM DEXRON III, Ford MERCON,
- Toyota T, T-II, T-III, T-IV
- 4,5 Speed BMW, MB,VW,
- Allison C-4, JASO M315 Type 1A
- Voith/MAN Commercial ATs,
- Nissan Matic C,DJ
- Suzuki/Subaru ATF Oil, ZF TE-ML-14A
- Mazda ATF D-III, ATF M-3

Kixx ATF Multi is suitable for many OEM S/F



Kixx ATF Multi is a special blend of **high quality base stocks** with an **advanced additives system**