



# Material Safety Data Sheet (MSDS)

<b>Product</b>	<b>Kixx D1 C3 5W-30</b>		
<b>Team</b>	<b>Date of first preparation</b>	<b>Date of last revision</b>	<b>Revision Number</b>
<b>Finished Lubricants R&amp;D Team</b>	<b>2015-09-09</b>	<b>2017-10-26</b>	<b>2</b>

## 1. Chemical Product and Company Information

- 1) Product : Kixx D1 C3 5W-30
- 2) Recommended use of the chemical and restrictions on use
  - Recommended use : Internal combustion engine
  - Restrictions on use :
- 3) Manufacture/Supplier information
  - Supply company : GS Caltex Corporation
  - Address : Nonhyeon-ro 508(Yeoksam-dong), Gangnam-gu, Seoul, South Korea
  - Information service or emergency call : 82-2-1899-5145
  - Department in charge : Finished Lubricants R&D Team

## 2. Hazards Identification

- 1) Classification of the substance or mixture
  - Not hazardous
- 2) GHS labels, including precautionary statements
  - Symbol : No symbol
  - Signal word : No signal word
  - Hazard statement
    - Not classified under GHS criteria
  - Precautionary statement
    - Prevention
      - No precautionary phrases
    - Response
      - No precautionary phrases
    - Storage
      - No precautionary phrases
    - Disposal
      - No precautionary phrases
- 3) Other hazards which do not result in classification

---

### 3. Composition and Information on Ingredients

---

Component	Synonyms	CAS No.	Content(%)
1) Distillates, Hydrotreated Heavy Paraffinic	Hydrotreated (severe) heavy paraffinic distillate	64742-54-7	80 ~ 90
2) Additive for Engine Oil (S1)		Mixture	10 ~ 15
3) Viscosity Modifier Mixture (S2)		Mixture	5 ~ 10

---

### 4. First Aid Measures

---

- 1) Eye contact :
  - Wash eyes thoroughly with plenty of water for at least 20 minutes.
  - If persistent irritation occurs, obtain medical attention.
- 2) Skin contact :
  - Remove contaminated clothing and wash skin with plenty of soap and water.
  - Flush with plenty of water for 15 minutes.
  - Seek medical attention if ill effect or irritation develops.
- 3) Inhalation :
  - If overcome by exposure, remove person to fresh air immediately.
  - Give oxygen or artificial respiration as needed.
  - Obtain emergency medical attention. Prompt action is essential.
- 4) Ingestion :
  - Do not induce vomiting. In general no treatment is necessary unless large quantities are swallowed
  - Obtain emergency medical attention. Prompt action is essential.
- 5) Most important symptoms/effects, acute and delayed :
  - May cause slight eye and skin irritation. Not expected to be a sensitizer.
- 6) First-aid treatment and information on medical doctors :
  - Treat symptomatically.
  - Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

---

### 5. Fire Fighting Measures

---

- 1) Recommended(or prohibited) extinguishing media
  - Recommended extinguishing media :
    - Dry chemicals, CO<sub>2</sub>, water spray, fire fighting foam
  - Prohibited extinguishing media :
    - High pressure water shoot
  - Large fire :
    - Use water spray, water fog or alcohol-resistant foam

2) Specific hazard from chemical material

- Toxicant from combustion : Carbon oxides
- Fire and Explosion Hazards: Slight fire risk

3) Extinguishment :

If it is not dangerous, remove containers from fire areas.

Make hills for further treatment.

avoid Inhalation of material oneself or combustion generation material

Stand against the wind and avoid lower zone.

---

## 6. Accidental Release Measures

---

1) Necessary actions to protect human health :

- If it is not dangerous, stop release safely, do so.

Wear protective gloves, apron, boots, head and face protection should be worn, If need.

Keep away from water supply facilities and sewage.

Avoid inhalation of materials or combustion products.

Avoid heat, flame, spark, and other ignition sources.

2) Necessary actions to protect the environment

- May contaminate water supplies/pollute public waters. Evacuate/limit access.

Equip responders with proper protection.

Prevent flow to sewer/public waters. Stop release. Notify fire and environmental authorities.

Restrict water use for cleanup.

3) Purification and removal methods

- Small leak : Only authorized person can access to the hazardous and restricted areas.

Collect spills with proper containers to treat them.

Absorb spills with sand and other non-combustible materials.

- Large leak : No data

---

## 7. Handling and Storage

---

1) Safety handling :

Avoid prolonged or repeated contact with skin. Use proper bonding and/or grounding procedures.

Prevent small spills and leakage to avoid slip hazard. Avoid inhaling vapour and/or mists.

Material can accumulate static charges which may cause an electrical spark (ignition source).

2) Storage :

Storage in closed containers.

Storage in cool and dry areas.

Ventilation keeps it in a region

Keep away from prohibited materials for mixing.

---

## 8. Exposure Control and Personal Protection

---

A. Exposure limits and biological exposure limits of chemical

1) Distillates, Hydrotreated Heavy Paraffinic

- ACGIH : No data
- OSHA : No data
- NIOSH : No data
- AHIA : No data
- Biological exposure limits : No data

2) Additive for Engine Oil (S1)

- ACGIH : No data
- Biological exposure limits : No data

3) Viscosity Modifier Mixture (S2)

- ACGIH : TWA(5mg/m<sup>3</sup>)
- OSHA : TWA(5mg/m<sup>3</sup>)
- NOHSC : TWA(5mg/m<sup>3</sup>, 8hr)

B. Engineering management :

Ventilation equipment should be explosion-proof if explosive concentrations of dust, vapor or fume are present.

Install local ventilation system.

Comply with limits.

C. Personal protection equipment :

- Respiratory protection :

If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate.

Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Half-face filter respirator

- Eyes protection :

Safety glasses or goggles are recommended for the eyes protection from dusts or mists. A business proprietor should install eyes washing facilities near working areas to protect worker's eyes for emergency.

- Hands protection :

Use proper chemical resistant gloves.

- Human body protection :

Use proper chemical resistant clothes based on published literature or manufacturer data.

---

## 9. Physical and Chemical Properties

---

1) Appearance : Clear, light yellow liquid

2) Odor : a specific smell of Hydrocarbon

3) Odor threshold : No data

4) pH : No data

- 5) Melting point/freezing point : No data
- 6) Initial boiling point or boiling range : > 280°C
- 7) Flash point : 226°C (C.O.C)
- 8) Evaporation rate (BuAc=1) : No data
- 9) Flammability(solid, gas) : No data
- 10) Upper/lower flammability or explosive limits : No data
- 11) Vapor pressure : <0.1 Kpa @ 20°C
- 12) Solubility : No data
- 13) Vapor density : No data
- 14) Relative density : 0.85
- 15) Partition coefficient: n-octano/water : No data
- 16) Auto-ignition temperature : No data
- 17) Decomposition temperature : No data
- 18) Viscosity : 12.09cSt(100°C)
- 19) Molecular weight : No data

---

## 10. Stability and Reactivity

---

- 1) Chemical stability :
  - Stable at room temperature and pressure.
- 2) Toxicant generation possibility during reaction :
  - No data
- 3) Prohibited conditions :
  - Avoid heat, sparks, open flames and other ignition sources
- 4) Prohibited materials :
  - An Oxidizing agent
- 5) Toxicant during decomposition :
  - Carbon oxides, Hydrogen sulfide

---

## 11. Toxicological Information

---

### A. Information on the likely routes of exposure

- Inhalation : May cause slight irritation
- Ingestion : May cause vomit, coughing, shortness of breath, dizziness.
- Skin contact : May cause slight skin irritation.
- Eye contact : May cause slight eye irritation.

### B. Delayed and immediate effects and chronic effects from short or long term exposure

#### 1) Distillates, Hydrotreated Heavy Paraffinic

- Acute Toxicity
  - Oral : Not determined / LD 50 > 5000 mg/kg bw : rat
  - Dermal : Not determined / LD 50 > 5000 mg/kg bw : rabbit
  - Inhalation : category 4 / LC 50 = 2.18 mg/l (4hr) : rat
- Skin Corrosion / irritation : No irritating (Rabbit)
- Severe eye Damage/irritation : no irritating (rabbit)
- Respiratory sensitization : Not determined
- Skin sensitization : Not determined
- Carcinogenicity : MOL, OSHA, IARC : No data
- Germ cell mutagenity : Negative (Ames test)
- Reproductive Toxicity : No data
- Specific target organ Toxicity(single exposure) : No data
- Specific target organ Toxicity(repeated exposure) : No data
- Aspiration toxicity : No data

#### 2) Additive for Engine Oil (S1)

- Acute Toxicity
  - Oral : No data
  - Dermal : No data
  - Inhalation : No data
- Skin Corrosion / irritation : No data
- Severe eye Damage / irritation : No data
- Respiratory sensitization : No data
- Skin sensitization : No data
- Carcinogenicity : No data
- Germ cell mutagenity : No data
- Reproductive Toxicity : No data
- Specific target organ Toxicity(single exposure) : No data
- Specific target organ Toxicity(repeated exposure) : No data
- Aspiration toxicity : No data

#### 3) Viscosity Modifier Mixture (S2)

- Acute Toxicity
  - Oral : LD50 in rats is > 2000 mg/Kg
  - Dermal : LD50 in rabbits is > 2000 mg/Kg
  - Inhalation : No data

- Skin Corrosion / irritation : Not expected to be a primary skin irritant.  
Based on data from similar materials. Prolonged or repeated skin contact as from with material may cause dermatitis. Symptoms may include redness, edema, drying, and
- Severe eye Damage / irritation : No data
- Respiratory sensitization : No data
- Skin sensitization : No data
- Carcinogenity : This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have demonstrated to contain less than 3% extractables by the IP 346 test.
- Germ cell mutagenity : No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
- ReproductiveToxicity : No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity.
- Specific target organToxicity(single exposure) : No data
- Specific target organToxicity(repeated exposure) : No data
- Aspiration toxicity : No data

C. Numerical measures of toxicity(such as ATE) : No data

---

## 12. Ecological Information

---

A. Aquatic, terrestrial organisms toxicity :

- 1) Distillates, Hydrotreated Heavy Paraffinic
  - No data
- 2) Additive for Engine Oil (S1)
  - No data
- 3) Viscosity Modifier Mixture (S2)
  - The acute LC50 is 100 – 1000 mg/L based on component data.

B. Persistence and degradability :

- 1) Distillates, Hydrotreated Heavy Paraffinic
  - No data
- 2) Additive for Engine Oil (S1)
  - No data
- 3) Viscosity Modifier Mixture (S2)
  - No data

C. Bioaccumulative potential

- 1) Distillates, Hydrotreated Heavy Paraffinic
  - Contains components with the potential to bioaccumulate.
- 2) Additive for Engine Oil (S1)
  - No data
- 3) Viscosity Modifier Mixture (S2)
  - No data

D. Mobility in soil :

- 1) Distillates, Hydrotreated Heavy Paraffinic

- Expected to have mobility in soils.
  - 2) Additive for Engine Oil (S1)
    - No data
  - 3) Viscosity Modifier Mixture (S2)
    - No data
- E. Other adverse effects :
- No data

---

## 13. Disposal Considerations

---

- 1) Disposal methods :  
Use only licensed transporters and permitted facilities for waste disposal.
- 2) Disposal cautions :  
Dispose according to the related regulations

---

## 14. Transport Information

---

- 1) UN number : Not applicable
- 1) UN number : Not applicable
- 2) UN Proper Shipping Name : Not applicable
- 3) Transport hazard classes : Not applicable
- 4) Packing group, if applicable : Not applicable
- 5) Environmental hazards : Not applicable
- 6) Special precautions for user : Not applicable
- 7) This product is not regulated as a hazardous material by the IATA transportation regulations.

---

## 15. Regulatory Information

---

- A. Industrial safety and health act (Korea)  
Occupation environment measurement material, Special health examination material,  
Threshold limit values material.
- B. Chemical control act (Korea)
  - No data
- C. Dangerous Goods Safe Control Act (Korea)  
Category 4 Dangerous Goods (Flammable Liquids), Grade 4 petroleum chemicals
- D. Hazardous material safety act (Korea)



- No data

E. Other internal and foreign acts

- Not determined

---

## 16. Other Information

---

1) References

- Korea Occupational Safety & Health Agency
- GS Caltex R&D Center
- MSDS of raw material from supplier
- KOSHANET
- Occupation safety and health acts of Korea
- Globally Harmonized System of classification and labeling of chemicals (GHS), First revised edition, United Nations
- EINECS(European Inventory of Existing Commercial Chemical Substances)
- ACGIH(American Conference of Governmental Safety and Health)
- IUCLID Dataset

2) Date of preparation of the first version of the MSDS : 2015.09.09

3) Revised frequency and Date of preparation of the latest version of the MSDS : 2017-10-26 (2)

4) Others :

To the best of our knowledge, the information provided in this MSDS document is correct. Access to this information is being provided via the Internet so that it can be made available to as many potential users as possible. We do not assume any liability for consequences of the use of this information since it may be applied under conditions beyond our control or knowledge. Also, it is possible that additional data could be made available after this MSDS was issued.

Certain hazards are described herein, however these may not be the only hazards that exist. All materials may present unknown hazards and should be used with caution.

Customers are encouraged to review this information, follow precautions, and comply with all applicable laws and regulations regarding the use and disposal of this product.

For specific technical data or advice concerning this product as supplied in your country please contact your local sales representative.

The final determination of the suitability of any material is the sole responsibility of the user.