



# RED LINE SUPER LIGHTWEIGHT SHOCKPROOF®



- Film thickness greater than an SAE 75W90, yet low fluid friction like ATF
- Used in low-power dog-ring racing transaxles with moderate to low load, qualifying, etc.
- Popular in British F3, Euro F3 and Star Mazda racing gearboxes for ultra low drag

## RECOMMENDED FOR:

CIRCLE TRACK  
ROAD RACING  
DRAG RACING  
OFF ROAD  
OTHER WET-SUMP SPLASH APPLICATIONS

## PACKAGE SIZES:

58504 - SuperLight ShockProof Gear Oil - quart  
58505 - SuperLight ShockProof Gear Oil - gallon  
58506 - SuperLight ShockProof Gear Oil - 5 gallon

## ABOUT RED LINE SHOCKPROOF GEAR OILS

- Unique lubricant with solid microscopic particles offers low drag/high protection
- Relatively low viscosity, yet cushions gear teeth under extreme pressure
- Helps to prevent tooth breakage, resists throw-off
- Avoid use with pumps, coolers, and filters as unique medium and affinity for metal can cause clogging
- Designed for wet sump transmissions and differentials with splash lubrication

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM