



FICHE TECHNIQUE
v072017

ATF 8 Gear

DESCRIPTION: High quality synthetic automatic transmission fluid with low viscosity for a more responsive transmission. Suitable for automatic transmissions.

APPLICATION: Bardahl ATF 8 Gear has excellent stability and fluidity at low temperatures. Ideal for cold starts. The ATF 8 GEAR can be used in many automatic transmissions and has been formulated for the lubrication of ZF 8HP (8HP45, 8HP55, 8HP70, 8HP90 ...) transmissions as it has a strong fuel economy contribution. It can also be used for some 6HP (VAG, BMW models).

SPÉCIFICATIONS : the product meets the performance levels listed below:

VAG	G 052 533 / G 055 005 / G 055 540 / G 055 162 / G 060 162
BMW	83 22 0 142 516 / 83 22 2 152 426 / 83 22 0 397 114 /163 514
MB	236.12/236.14/236.15/236.41
JAGUAR	FLUID 8432
MITSUBISHI	ATF - J3
MAZDA	FZ
MERCON	LV
GM	DEXRON VI/AW1
JASO	M315 Class 1A
TOYOTA	TYPE WS
AISIN WARNER	JWS 3324
NISSAN	MATIC S
SHELL	M-1375.4 / 3354
FORD	XT-6-QSP
HONDA	ATF-DW1
HYUNDAI	SP-IV / SPH-IV

ATF 8 Gear

SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



PROPRIÉTÉS

- ✓ High viscosity index ensuring good stability,
- ✓ Longer life,
- ✓ **Very low pour point,**
- ✓ Very good thermal stability,
- ✓ Very good anti-oxidation protection,
- ✓ Anti-wear, anti-corrosion and anti-foam,
- ✓ High-performance anti-friction additives,
- ✓ Inert for seals and non-ferrous metals,
- ✓ Good resistance to vibrations,
- ✓ Quick commissioning during cold starts,
- ✓ Viscosity to avoid over-consumption (fuel economy),
- ✓ Dark yellow color.

DONNÉES TECHNIQUES

Density at 15°C	Kg/l	0,843
Viscosity 40°C	mm ² /s	30
Viscosity 100°C	mm ² /s	6,1
Viscosity Index		155
Flash point COC, °C	°C	>200
Pour point, °C	°C	-42
Alkalinity TBN	mgKOH/g	n/A

RECOMMANDATIONS Handling: All safety information on the handling and use of this product is provided in the Material Safety Data Sheet. Consult the manufacturer's manual. Storage: it is recommended to use the product within 60 months. It must be stored in the original sealed packaging, protected from light, moisture and excessive temperatures.

REFERENCES & PACKING

36871	12 x 1L
36873	3 x 5L
36878	20L
36874	60L
36877	205L

SADAPS BARD AHL ADDITIVES & LUBRICANTS