

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.



Lubricants - Engine Oil - Passenger Car Motor Oils

Version: 045/01d

Valvoline™ All-Climate Motor Oil SAE 5W-30

High quality full synthetic motor oil. Formulated for year round performance. Proven and trusted technology for a broad range of diesel, petrol and LPG engines.

Performance levels
ACEA A3/B3, A3/B4
API: SN
MB-229.3
VW 50200/50500
Recommended for use where Fiat 9.55535.G1 is specified.

Applications

Formulated for petrol, diesel and LPG engines of passenger cars, delivery vans, persons minibuses, campers.

For modern engines with turbochargers, catalytic converters and long drain intervals.

Features & Benefits

Year round performance

All-Climate engine oils are formulated for year round performance. Meeting industry performance levels.

Broad vehicle application

High quality formulation suitable for a wide range of vehicles.

Cold start performance

Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

Wear protection

Strong oil film provides protection against wear under all operating conditions.

Engine cleanliness

Through the use of detergent additives the engine is kept in good condition. Exceeds the ACEA A3/B3 limits for piston cleanliness in the Volkswagen TDI engine test.

Deposit control

Prevents forming of sludge and harmful deposits inside the engine.

Breakdown resistance

Thermal and oxidation stable oil film resists oil breakdown.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health & Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Safety Data Sheet (SDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Author:

AdG

Replaces –

All-Climate Motor Oil	
SAE viscosity grade	5W-30
Viscosity , mm ² /s @ 100 °C. ASTM D-445	12,0
Viscosity , mm ² /s @ 40 °C. ASTM D-445	72
Viscosity Index ASTM D-2270	165
Viscosity , mPa.s –30°C. ASTM D-5293	<6600
TBN , mg KOH/g ASTM D-2896	10,8
Pour Point , °C ASTM D-5949	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0,854
Flash Point , COC, °C. ASTM D-92	230

This information only applies to products manufactured in the following location(s):
Europe

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2015, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.