

Aral Getriebeöl EP Plus 80W-90

Universal Fluid for manual transmissions and axles



Description

Aral Getriebeöl EP Plus 80W-90 is a part-synthetic SAE 80W-90 multipurpose manual transmission and final drive lubricant. It is particularly recommended for use in highly loaded final drives and differentials of commercial vehicles where API GL-5 performance is required and it carries a number of OEM approvals. Additionally it may be used in synchronised manual transmissions requiring API GL-4 or GL-5 fluids.

Advantages

- A single product for transmissions and final drives reducing inventory and the potential for misapplication
- High temperature stability gives superior performance and extended drain potential.
- Proven performance as a problem solver in differentials operating in hot climates under arduous conditions.
- Optimised synchroniser performance gives smooth gear shifting at all temperatures.
- High shear stability maintains performance over the life of the lubricant.
- Excellent wear protection particularly at high temperatures extends component life and reduces maintenance costs

Typical Characteristics

Name	Method	Units	Getriebeöl EP Plus 80W-90
Density @ 15C, Relative	ASTM D4052	g/ml	0.896
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	145
Viscosity Index	ASTM D2270	None	99
Pour Point	ASTM D97	°C	-27
Viscosity, Brookfield @ -26C (80W)	ASTM D2983	mPa.s (cP)	< 150.000
Flash Point, COC	ASTM D92	°C	226

Product Performance Claims

API GL-4/ GL-5/ MT-1

MAN 341 Z2,

MAN 342 M2

ZF TE-ML 02B, 05A, 12L, 12M, 16B, 17B, 19B, 21A

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Getriebeoel EP Plus 80W-90

29 Nov 2016

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

www.aral-lubricants.de