elf
A brand of TOTAL

EVOLUTION 700 ST
15W-50

ELF Evolution 700 ST 15W-50 is a multigrade oil designed for the most recent and highest performance Gasoline engines, whose formulation uses a combination of mineral bases and selected synthetic oils.

APPLICATIONS

All Gasoline engines	• Recommended for all Gasoline and Diesel engines in private cars, MPVs and light vans.
High speed / Urban driving	• Allows extended use both at high speed for "vigorous" applications and in urban driving, and ensures optimal engine operation whatever the temperature.
Any time of year	• Can be used throughout the year.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

Spécifications internationales	ACEA : A3/B4 API : SL/CF
Homologations constructeurs	VOLKSVAGEN VW 501.01 / 505.00 MERCEDES BENZ MB-Approval 229.1

CUSTOMER BENEFITS

Highly tenacious oil film	• Excellent lubricating properties both hot and cold, ensuring in particular a tenacious oil film at high temperature. • Very high detergent-dispersant capability, keeping engine components perfectly clean and giving very effective protection against the formation of black sludge.
Engine protection	• Outstanding thermal stability and oxidation resistance, preventing any premature degradation. • Outstanding protection against wear, particularly in the timing system.
Engine protection	• Excellent anticorrosion and antifoaming properties. • High viscosity number and high shear stability thanks to the use of special bases and selected viscosity additives, ensuring the best possible performance in service.

CHARACTERISTICS

	Method	Units	SAE Grade 15W-50
Density at 15°C	ASTM D1298	kg/m^3	893,4
Viscosity at 40°C	ASTM D445	mm^2/s	170,6
Viscosity at 100°C	ASTM 445	mm^2/s	18,7
Viscosity index	ASTM D2270	-	147
Pour point	ASTM D97	°C	- 30
Flash point	ASTM D92	°C	252

The typical characteristics mentioned represent mean values

afaq
ISO 9001
Qualité
AFNOR CERTIFICATION