



KOKYBĖS SERTIFIKATAS
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

Date: 2016 09 02			
FANFARO SN for HONDA 5W-30			
PRODUCT DESIGNATION	API SN/ILSAC GF-5		
Control Item	Standard	Results	Test Method
Viscosity at 100 °C, cSt	11-12	11.58	ASTM D-445
Viscosity at 40 °C, cSt	-	70.02	ASTM D-445
Dynamic viscosity [mPa.s], at -30 °C, max.	6600	6262	ASTM D 5293
Viscosity Index, min.	160	160	ASTM D-2270
Flash point, open cup, °C	210	224	ASTM D-92
Pour point, °C, max.	-30	-42	ASTM D-97
Total base no. mgKOH/g, min	8,0	8.59	ASTM D-2896
Density at 15 °C, kg/l, max.	0.9	0,850	ASTM D-1298

Responsible analyst: Daiva Burbaite

UAB "SCT LUBRICANTS"

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA
TEL.(8 46) 34 03 45, FAKS. (8 46) 34 18 91
E-MAIL: KLAIPEDA@SCT.LT