



# Gear Oil 90

**Non Extreme pressure lubricant**

**Mechanical transmissions lightly loaded**

## TYPE OF USE

All mechanical transmission, manual gearboxes and differentials operating under mild loads and low revolution speed and moderate temperatures designed to use a straight mineral oil.

Recommended for transmissions or manual gearboxes of some trucks and buses VOLVO, TERBERG, SEDDON ATKINSON, LEYLAND TRUCK-SCAMMEL, LEYLAND DAF and FORD (GB).

## PERFORMANCES

STANDARDS :            API GL-1

Straight pure mineral oil with :

- Rust inhibitor
- Oxidation inhibitor
- Foaming inhibitor

Does not contain any friction modifier.

## RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

## PROPERTIES

Viscosity grade	SAE J 306	<b>90</b>
Density at 20°C (68°F)	ASTM D1298	0.893
Viscosity at 40°C (104°F)	ASTM D445	150 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	15 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	100

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site : [www.motul.fr](http://www.motul.fr)

09/10