



your local global brand

# Formula PCX 5W-30

*Synthetic MID SAPS Motor Oil*

## **Product Description**

**Gulf Formula PCX 5W-30** is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a PSA B71 2290 specification is required and suitable for all engines which require an C2 performance specification.

**Gulf Formula PCX 5W-30** is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

**Gulf Formula PCX 5W-30** exceeds the following performance criteria

API SN/CF                      ACEA C2                      Renault 0700                      PSA B71 2290

## **Typical Analysis**

<b>Properties</b>	<b>Unit</b>	<b>Method</b>	<b>Typical Value</b>
SAE Grade		SAE J 300	5W-30
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	856
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	70
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	11.8
Viscosity Index		ASTM D2270	170
Viscosity CCS -30°C, max	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	7.5
Sulphated Ash	%Wt	ASTM D874	0.79

<b>Product Code: 1219</b>	Date Issued: 13-08-2012	Date Reviewed:	Revision: -
---------------------------	-------------------------	----------------	-------------