

# NIPPON ATF

## SYNTHETIC AUTOMATIC TRANSMISSION FLUID

### DESCRIPTION

Top tier synthetic automatic transmission fluid. Designed for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications.

### PROPERTIES

- Very high and stable viscosity index.
- Very low pour point.
- Excellent oxidation stability.
- Outstanding anti-wear properties.
- Outstanding performances at cold start conditions.
- Specific friction properties and consequently low noise and smooth switching.



### APPLICATION

For automatic gearboxes, power steering units, torque converters and other equipment. Apply the correct amount of oil indicated in the service instructions of the manufacture. Wrong amount of oil can cause damage to the transmission.

### TYPICALS

Density at 15 °C, kg/l	0,846
Viscosity at 40 °C, mm <sup>2</sup> /s	36,60
Viscosity at 100 °C, mm <sup>2</sup> /s	7,20
Viscosity index	165
Flash point COC, °C	212
Pour point, °C	-48
Total Base Number, mgKOH/g	2,7

### PACKAGING

1L can (12 x 1L carton)  
4 L can (4 x 4L carton)  
60 L drum  
208 L drum

### SPECIFICATIONS

Toyota T, T-II, T-III, T-IV, D-II, D-III, WS  
Nissan Matic Fluid C, D, J  
Nissan CVT Fluid NS-1, NS-2  
Honda Ultra II, Ultra Z-1, Ultra HMMF  
Mazda M-III, D-II, M-V, F-1  
Mitsubishi SP-II, SP-III, ATF-II, ATF-SK  
Suzuki ATF Oil, ATF Oil Special  
Subaru ATF, Kia, Isuzu Besco ATF II, III  
Daihatsu Alumix ATF Mullti  
GM TASA, IID, III  
VW/AUDI G-055-025-AZ  
Mercon, Allison C-4  
JASO M 315 Type 1A

Also suitable for use in:

Hyundai ATF SP-IV  
JWS 3309, 3317  
MB 236.6, 236.7, 236.8  
MB 236.9, 236.10  
BMW 7045E  
Chrysler ATF, ATF +3, ATF +4