

# OEM-LINE 5W30 GM DEXOS 2

## HIGH PERFORMANCE SYNTHETIC ENGINE OIL

### DESCRIPTION

A universal, synthetic fuel economy motor oil developed according the most recent technology. Based on specially selected base oils with a high natural viscosity index with the addition of a well-balanced choice of advanced additives.

### PROPERTIES

- Lower fuel consumption.
- High and very stable viscosity index.
- High resistance against shearing.
- Fast cold start.
- Safe lubrication film at very high temperatures.
- Reduced formation of combustion ashes.
- Very good detergency and dispersion.
- Very strong protection against wear, corrosion and foaming.



### APPLICATION

This universal fuel saving synthetic motor oil is specially developed for passenger car unit injector diesel engines. Moreover this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application. Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

### TYPICALS

Density at 15 °C, kg/l	0,851
Viscosity -30 °C, mPa.s	6136
Viscosity 40 °C, mm <sup>2</sup> /s	72,60
Viscosity 100 °C, mm <sup>2</sup> /s	12,50
Viscosity Index	172
Flash Point COC, °C	230
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,4
Sulphate Ash, %	0,78

### SPECIFICATIONS

ACEA C3-12
API SN
MB-Approval 229.51/229.52
Approved under VW 502.00/505.00/505.01
Dexos 2
BMW Longlife-04

### PACKAGING

1L can (12 x 1L box)  
5L can (4 x 5L box)  
60 L drum  
208 L drum