

Safety Data Sheet according to EC-Regulation 91/155/EEC

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

OLYMPIA HYPOID SUPER GEAR GL-5 SAE 80W-90

Art.: 2126.119

Use of the substance/preparation

Refer to description of material or preparation.

Company/undertaking identification

OLYMPIA Lube Oil FZCO, P.O.Box 17533 Jebel Ali - Free Zone, Dubai - U.A.E

Telephone +971 4 8817334, Fax +971 4 8817335

olo@emirates.net.ae www.olympiaoil.com

Emergency telephone / Office for advice

Advisory office in case of poisoning:

Tel.: ---

Telephone number of the company in case of emergencies:

Tel. +971 50 2449093

2. Composition/information on ingredients

2.1 Chemical name	content %	symbol	R-phrases	EINECS, ELINCS
Baseoil - unspecified	30 - 80	---	---	276-736-3
Hydrocarbon mixture, paraffinic	20 - 60	---	---	276-735-8
Phosphoric acid ester amine salts	1 -< 2,5	N	51-53	
Olefin sulfide	1 - 5	---	53	

For complete wording of the R-phrases, refer to point 16.

3. Hazards identification

3.1 To people

See point 11 and 15.

Preparation is not classified as hazardous in the sense of directive 1999/45/EC.

3.2 To the environment

See point 12.

Product can compose a film on the water surface, which can prevent oxygen exchange.

4. First aid measures

4.1 Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

4.3 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

4.4 Ingestion

Do not induce vomiting. Consult doctor immediately.

4.5 Special resources necessary for first aid

n.g.

5. Fire-fighting measures

5.1 Suitable extinguishing media

CO2
Foam
Dry extinguisher
Water jet spray

5.2 Extinguishing media which must not be used for safety reasons

High volume water jet

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Oxides of carbon
Oxides of nitrogen
Oxides of sulphur
Hot product gives off combustible vapours.
Flammable vapour/air mixtures.

5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply
According to size of fire
Full protection, if necessary

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

6. Accidental release measures

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Avoid formation of oil mist.
Remove possible causes of ignition - do not smoke.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping.
Do not carry cleaning cloths soaked in product in trouser pockets.

6.2 Environmental measures

If leakage occurs, dam up.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods for cleaning up

Collect using absorbant material (e.g. Universal binding medium), and dispose of according to point 13.

7. Handling and storage

7.1 Handling

Tips for safe handling:

See point 6.1
Ensure good ventilation.
Keep away from sources of ignition - Do not smoke.
Wash hands before breaks and at end of work.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
General hygiene measures for the handling of chemicals are applicable.
Observe directions on label and instructions for use.
Do not heat to temperatures close to flash point.
Take measures against electrostatic charging, if appropriate.
If applicable:
Use explosion-proof equipment.
Exposed employees should have regular medical check-ups.

7.2. Storage

Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.
Store products only unopened, in original packing.
Do not store with flammable or self-igniting materials.

Special storage conditions:

See point 10.2
Protect against moisture and store closed.

8. Exposure controls/personal protection

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Chemical Name	Baseoil - unspecified	
WEL-TWA: ** 70 ppm (350 mg/m ³) (AGW)	WEL-STEL: ** 4 (AGW)	---
BMGV: ---	Other information: ---	
Chemical Name	Hydrocarbon mixture, paraffinic	
WEL-TWA: ** 70 ppm (350 mg/m ³) (AGW)	WEL-STEL: ** 4 (AGW)	---
BMGV: ---	Other information: ---	
Chemical Name	Oil mist, mineral	
WEL-TWA: 5 mg/m ³ (ACGIH)	WEL-STEL: 10 mg/m ³ (ACGIH)	---
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AG = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BG = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

- 8.1 Respiratory protection: Normally not necessary.
With oil mist formation
If OES or MEL is exceeded.
Filter A P 3 (EN 141)
- 8.2 Hand protection: Protective nitrile gloves (EN 374)
Protective hand cream recommended.
- 8.3 Eye protection: Tight fitting protective goggles (EN 166) with side protection, with danger of projections.
- 8.4 Skin protection: Protective working garments (e.g. safety shoes EN 344, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.

Selection made for preparations according to the best available knowledge and information on the ingredients.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

9. Physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
10 % pH-value:	n.v.
Boiling point/range (°C):	n.v.
Melting point/range (°C):	- 20 - -30 (PP)
Flash point (°C):	190 - 210
Autoflammability:	n.g.
Minimum limit of explosion:	n.a.
Maximum limit of explosion:	n.a.
Vapour pressure:	n.g.
Density (g/ml):	0,9 - 0.915
Solubility in water:	Insoluble
Viscosity:	85W90 201mm ² /s/40°C 17,5mm ² /s/100°C, 80W90 147mm ² /s/40°C 15,1mm ² /s/100°C, 85W90LS 190mm ² /s/40°C 17,6mm ² /s/100°C

10. Stability and reactivity

10.1 Conditions to avoid

See point 7

Stable when handled and stored correctly.

Protect from humidity.

Open flame, ignition sources

10.2 Materials to avoid

See point 7

Avoid contact with strong oxidizing agents.

Avoid contact with other chemicals.

10.3 Hazardous decomposition products

See point 5.3

11. Toxicological information

11.1 Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg): n.v.

Inhalation, LC50 rat inhal.(mg/l/4h): n.v.

Skin contact, LD50 rat dermal (mg/kg): n.v.

Eye contact: n.v.

11.2 Delayed and chronic effects

Sensitization: n.g.

Carcinogenicity: n.g.

Mutagenicity: n.g.

Reproductive toxicity: n.g.

Narcosis: n.g.

11.3. Further information

No classification according to calculation procedure.

The following may occur:

May cause sensitization by skin contact.

Drying of the skin.

Irritation of the skin.

12. Ecological information

Water hazard class (Germany): 2

Self classification: Yes (VwVwS)

Persistence and degradability: Potentially biologically degradable.

Behaviour in sewage plants: n.v.

Aquatic toxicity: n.v.

Ecological toxicity: n.v.

13. Disposal considerations

13.1. for the material / preparation / residue

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations

Implement substance recycling.

E.g. suitable incineration plant.

13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

14. Transport information

General statements

UN-Number: n.a.

Road/Rail-transport (ADR/RID)

Class/packing-group: n.a.

Classification code: n.a.

LQ: n.a.

Transport by sea

IMDG-code: n.a. (class/packing-group)

Marine Pollutant: n.a.

Transport by air

IATA: n.a. (class/secondary danger/packing-group)

Additional information:

Non-dangerous material according to Transport Regulations.

15. Regulatory information**Classification according to Dangerous Product Regulations incl. EC Directives****(67/548/EEC and 1999/45/EC)**

Symbols: Not applicable

Indications of danger: ---

R-phrases:

S-phrases:

Additions:

Safety data sheet available for professional user on request.

Contains

Alkenyl amine

Substituted thiazazole

May produce an allergic reaction.

Observe restrictions: n.a.

16. Other information

These details refer to the product as it is delivered.

Storage class VCI (Germany): 10

Revised points: 8

The following phrases represent the prescribed R-phrases for the ingredients (designated in point 2).

51 Toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

Legend:

n.a. = not applicable / n.v., k.D.v. = not available / n.g. = not checked

OES = Occupational exposure standard / MEL = Maximum exposure limit / BMGV = Biological monitoring guidance value

AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Beim Staumberge 3, D-32839 Steinheim, Tel.: 01805-CHEMICAL / 01805-243 642, Fax: 05233-941790

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.