



Castrol EDGE Professional E 0W-20

Strength to Perform - Freedom to Drive

Description

Castrol EDGE Professional with *Titanium Fluid Strength Technology™* is Castrol's strongest and most advanced range of engine oils.

Infused with Liquid Titanium, this adaptive strength technology reduces metal to metal contact across a range of different driving speeds.

Castrol EDGE Professional - lowers friction and maximises engine performance.

Castrol EDGE Professional E 0W-20 gives you the confidence to demand maximum engine performance from today's latest technology, highly engineered engines that operate with tighter tolerances, requiring lowest viscosity oils.

Castrol EDGE Professional E 0W-20 is proven in tests to deliver outstanding oil strength.

Micro-filtered and with its signature fluorescent colour it is your guarantee of Professional quality.

Castrol EDGE Professional. Strength to Perform - Freedom to Drive.

Application

Castrol EDGE Professional E 0W-20 is suitable for use in Jaguar and Land Rover vehicles that require a 0W-20 lubricant that Meets ST JLR.51.5122 specification.

Advantages

Castrol EDGE Professional E 0W-20:

- Independently proven to improve engine efficiency
- Maximises short and long term engine performance
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Reduces engine deposits to maximise engine response

Typical Characteristics

Name	Method	Units	EDGE Professional E 0W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.8421
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.0
Viscosity, CCS -35C	ASTM D5293	mPa.s (cP)	4400
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	42
Viscosity Index	ASTM D2270	None	170
Ash, Sulphated	ASTM D874	% wt	0.81
Pour Point	ASTM D97	°C	-54
Flash Point, PMCC	ASTM D93	°C	210

Product Performance Claims

ST JLR.51.5122.

Castrol EDGE Professional E 0W-20

10 Apr 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com