

Pentolub Performance 10W-40

Fuel Economy Engine Oil

Description

Pentolub Performance 10W-40 is a modern smooth run fuel economy engine oil, which shows through its semi HC-synthetic base oil composition in connection with a highly shear stable VI-improver a unique viscosity stability and high temperature resistance.

Pentolub Performance 10W-40 is based on a modern additive technology which provides a sound anti wear performance under highest requirements such as cold weather starts, stop and go and extreme motorway trips. The smooth running properties lead to a provable fuel saving.

Pentolub Performance 10W-40 is ideally an all-season engine oil, which can be used in gasoline and diesel engines with or without turbochargers.

It is miscible with all standard motor oils based on mineral, HC-synthetic or synthetic oils.

Quality Level

API SL/CF
ACEA A3/B4

Approvals

MB-Approval 229.1
VW-Specification 501 01 / 505 00

Product Classification

The product is not classified as dangerous.

Pentolub Performance 10W-40		Typical Data	
	Unit	Result	Method
Appearance		bright and clear	DIN 10964
Density at 15 °C	kg/m ³	880	DIN EN ISO 12185
Kinematic Viscosity at 100 °C	mm ² /s	14,1	DIN EN ISO 3104
Kinematic Viscosity at 40 °C	mm ² /s	96	DIN EN ISO 3104
Viscosity Index		151	DIN ISO 2909
Dynamic Viscosity at -25 °C	mPa*s	6650	DIN 51377
Pour Point	°C	-37	ISO 3016
Flash Point	°C	226	DIN EN ISO 2592

While handling lubricants the relevant safety rules have to be taken into account. For more detailed information please see the current safety data sheet for this product.

This product may not be available at all locations. For more information, please call us at +49 4103-9134-0 or visit us at www.pentosin.com
Due to continual product research and development, the information contained herein is subject to change without notification. Typical data may vary slightly.