17509 Lubmin

Tel.: +49 (0) 38354 179530 Fax: +49 (0) 38354 179579



Product certificate

AVENO Semi Synth. 10W-30 Item No.: 3011203

Description

AVENO Semi Synth. 10W-30 is a semi-synthetic high-performance, smooth-running engine oil for carburettor and diesel car engines with or without turbocharging and direct injection. Extended oil change intervals as per manufacturer's instructions.

AVENO Semi Synth. 10W-30 is characterised by its excellent cold starting properties, minimisation of fuel consumption, friction and wear.

With **AVENO Semi Synth. 10W-30**, a reliable and heavyduty engine oil has been developed.

Instructions for use

AVENO Semi Synth. 10W-30 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

AVENO Semi Synth. 10W-30 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

AVENO Semi Synth. 10W-30:

Specifications:

- ⇒ ACEA A3/B4
- ⇒ API SN Resource Conserving, API SM Energy Connserving
- ⇒ ILSAC GF-5

AVENO Semi Synth. 10W-30 is approved, tried and tested in engines requiring adherence to manufacturer's fluid specifications: Toyota, Nissan, HONDA, MITSUBISHI, MAZDA, Suzuki, Isuzu, Subaru, Daihatsu, KIA, Hyundai, SsangYong, Daewoo

Properties

AVENO Semi Synth. 10W-30 offers:

- ⇒ Excellent cold starting properties, even at low temperatures
- ⇒ A very stable viscosity behaviour and shear stability
- ⇒ Reduction of fuel consumption under all operating conditions
- ⇒ Very good detergent and dispersing properties
- ⇒ Neutrality towards sealants
- ⇒ Low evaporation, thus low oil consumption
- ⇒ Extensive protection against wear, corrosion and foaming
- ⇒ Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Colour	yellowish brown		visual
Density	865	kg/m³	EN ISO 12185
Viscosity at 100°C	10.1	mm²/s	DIN 51 562
Viscosity index	148		DIN ISO 2909
Pour point	-39	°C	DIN ISO 3016

All declared values are approximate and subject to standard production variations.