



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants - Engine Oil - Heavy Duty Engine Oils

Version: 112/07

All-Fleet™ Extreme engine oil SAE 10W-40

All Fleet Extreme SAE 10W-40 is a Super High Performance Diesel (SHPD) engine oil for use in heavy-duty turbo-diesel engines of trucks, buses and industrial engines. The oil is engineered with synthetic technology to meet the long-life requirements of major engine manufacturers and gives protection over a long time period. All-Fleet Extreme SAE 10W-40 fulfils the API CI-4 specification, which means that the oil can be used in engines with Exhaust Gas Recirculation (EGR) systems. The ACEA E7 specification shows that the oil is suitable for modern heavy duty engines, fitted with Selective Catalytic Reduction (SCR) systems for NO_x reduction. The oil is not intended for Diesel Particle Filter (DPF) after treatment systems. All-Fleet Extreme SAE 10W-40 is made with synthetic technology resulting in improved low temperature properties.

Approvals/Performance levels

SAE 10W-40
ACEA E7, E5, E2
API CI-4, CH-4, CG-4
MAN M 3275
MB-228.3
Volvo VDS-3
Renault RLD/RLD-2
Cummins CES 20076/77/78
Mack EO-N, EO-M Plus
MTU Type 2
Caterpillar ECF-2, ECF-1-a
Deutz DQC III-10
Global DHD-1

Applications

Suitable for heavy-duty mixed fleets.

Suitable for EGR and SCR after treatment systems -- **not** for DPF systems.

Suitable for extended oil drain intervals in heavy duty trucks, buses and off-road machinery.

Suitable for low temperatures.

Features and Benefits

Emission control

Recommend for trucks fulfilling the EU Euro emission requirements up to Euro 4 and 5 standards * (*please consult owner's manual before use)

OEM approved

Recommended and approved by many major heavy-duty engine manufacturers.

Clean engine

Superior performing additive system prevents soot and sludge formation, ring sticking and deposit buildup.

Oxidation control

Enhanced oxidation control at high temperatures and extended drain intervals

Long life

Made with highly effective dispersant technology for superior wear protection and engine cleanliness, resulting in maximized engine durability

Low temperature performance

Enhanced cold flow properties, meeting the stringent OEM and ACEA 2012 specifications



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Safety Data Sheet (SDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

SAE Viscosity Grade	10W-40
Viscosity, mm²/s @ 100 °C. ASTM D-445	14,8
Viscosity, mm²/s @ 40 °C. ASTM D-445	100
Viscosity Index ASTM D-2270	154
Viscosity, mPa.s -25°C. ASTM D-5293	<7000
TBN, mg KOH/g ASTM D-2896	10,4
Pour Point, °C ASTM D-5950	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0,868
Flash Point, COC, °C. ASTM D-92	231

**This information only applies to products manufactured in the following location(s):
Europe**

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 112/06

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2015, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.