



Product information

XTG Gear Oil 75W90 GL5 Synthetic LS

Bardahl XTG Gear Oil 75W90 GL5 LS Synthetic is a gear oil specially developed for limited-slip differentials. This oil can also be used in steering boxes, final drives, etc. when the manufacturer advises a GL-5 or MIL-L-2105 C/D type lubricant.

Bardahl XTG Gear Oil 75W90 GL5 LS Synthetic is formulated to meet the increasing severe requirements of modern gearboxes and transmissions. This oil has extreme anti-wear properties and is blended from premium quality synthetic base oils combined with a balanced package of additives. This unique combination makes gear changing easier and gives better and quicker lubrication at low and high temperatures.

This product has an outstanding high temperature stability, to ensure outstanding lubrication under high loads and at critical ambient temperature applications. Concurrently, it also provides exceptional low temperature fluidity at subzero temperatures.

This oil provides improved cleanliness of high-temperature components, protects seals and are recommended for year-round lubrication and heavy load carrying conditions. Simultaneously this oil provides increased gear life, extended drain performance and reduce maintenance and down time.

This oil meets the requirements of the manufacturers of passenger cars, tradesman vans and trucks and may be used all year round. Mixable with all other transmission fluids (with exception of automatic transmission fluids).

Specifications

API Service GL-5
MIL-L-2105 D
FORD M2C-108-C/SQM-2C-9003 AA
CS 3000B
MACK GO-G, GO-H
EATON/FULLER
ZF
IHC 135-H-EP
CLARK: MS 8

Analytical-data

	<u>75W90LS</u>
Viscosity;cst at 100°C	14.5
Viscosity;cst at 40°C	87
Viscosity Index	170

BARDAHL NL 6 OCD INTERNATIONAL

Maxwellstraat 41 - 2216GP Dordrecht - Postbus 9024 - 3301 AA Dordrecht

Tel (078) 6512322 - Fax (078) 6174848 - email: info@bardahl.nl - website: www.bardahl.nl

GB52500



Product information

Viscosity; cp at	-40°C/140.000
Straight Ash; wt. %	0.1
Sulphated Ash; wt. %	0.1
TAN;mg KOH/g ASTM D664	2.3
Pour point; °C	-42
Flashpoint;COC; °C	136
Firepoint;COC; °C	156
Colour ASTM D1500	2.5
Specific Gravity at 15/15°C	0.895

Article number 52501
Contents 500 ml

Article number 52551
Contents 1 litre

Article number 52555
Contents 5 litre

Article number 52582
Contents 25 litre

Article number 52586
Contents 60 litre