



# S-OIL SEVEN ATF DEXRON®-VI

## FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

### Product Description

S-OIL 7 ATF DEXRON®-VI is a high-performance automatic transmission fluid officially approved by General Motors for use in vehicles with automatic transmissions (J-60007). It is formulated with 100% synthetic base stocks and advanced additive technology. It is also fully back-serviceable and can be used wherever DEXRON-II and/or DEXRON III are recommended.

### Applications

- S-OIL 7 ATF DEXRON®-VI is recommended for all 2006 and beyond GM's vehicles with automatic transmissions.
- S-OIL 7 ATF DEXRON®-VI is also fully back-serviceable and can be used wherever DEXRON-II and/or DEXRON III are recommended.

### Features and potential benefits

- Extended drain intervals
- Consistent shift performance
- Protect against wear, corrosion, and the formation of harmful deposits such as lacquers and sludge
- Excellent thermal stability and resistance to oxidation
- Excellent viscosity stability in operation
- Exceptional friction and anti-shudder performances
- Enhanced fuel economies thanks to low viscosity and excellent low temperature performance

### Performance level

- GM DEXRON®-VI
- FORD MERCON®
- FORD M2C 138CJ, 166H
- Mercedes Benz 236.6,7,9
- JASO 1A-LV
- Honda DW-1
- HYUNDAI KIA SP-IV
- Mazda ATF FZ,F-1,S-1
- Mitsubishi Diaqueen J2,3,ATF PA
- NISSAN Matic K,S
- TOYOTA ATF T-IV,WS
- ZF TE-ML 09,09X,11A,11B

### Typical Properties

Test Items	Method	Unit	Typical properties	
Specific gravity	ASTM D1298	-	0.846	
Viscosity	40°C	ASTM D445	cSt	29.5
	100°C	ASTM D445	cSt	6.0
Viscosity index	ASTM D2270	-	159	
Flash point	ASTM D92	°C	222	
Pour point	ASTM D97	°C	-45	

S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul, 04196, Korea

S-OIL SEVEN ATF DEXRON®-VI  
2016.03.31.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.