



# S-OIL SEVEN *ATF Multi*

**FULLY SYNTHETIC Multi-purpose Automatic Transmission Fluid**

## Product Description

S-OIL 7 ATF Multi is a premium automatic transmission fluid based on highly refined API Group III base oil and suitable for use in wide range of Asian, European, American 4,5 and 6 speeds ATFs. Its excellent thermal and oxidation stability prevents deposit or corrosive matters in your gear box, so It provides stable operation of your ATF and long oil life.

## Applications

- 4/5/6-speed automatic gearboxes in Asian, European, American passenger vehicles

## Features and potential benefits

- Full synthetic base oil\* helps maintain oils initial conditions thanks to good stability and high viscosity index  
\*) S-OIL manufactures high quality API Group III base oil named "ULTRA-S" and provides it globally
- Exceptional friction and anti-shudder performances with advanced technology
- Excellent viscosity stability in operation
- Excellent thermal stability and resistance to oxidation
- Very good wear protection

## Performance level

- GM DEXRON II/IID/IIIE/IIIG/IIIH/VI, Ford Mercon, Allison C4/TES-295/TES-389, Land Rover Texaco N402
- Jaguar Idemitsu K17/Fluid 8432, Chrysler ATF+3/+4/SP-III, Esso LT 71141, JWS 3309
- SSANGYONG DSIH 5M-66, Hyundai Kia SP-II/III/IV, JASO M315 1A
- Toyota Type D-II/T/T-III/T-IV/T-WS, Mitsubishi J2/SP-II/SP-III, Mazda FZ/F-1/JWS3317/M-III/Type T-IV/M-V
- Nissan Matic-D/J/K/W/S, Subaru ATF; plus ATF-HP, Isuzu ATF II/III, Suzuki 3314/3317, Honda ATF Z-1/DW-1
- Volkswagen/Audi G052 025 A2/055/162(-A1/-A2)/533/990(A2)/G055 025(A2)
- BMW LT71141/LA2634/ETL-7045E/8072B, Mercedes Benz 236.3/5/6/7/8/9/10/11/91, Renault Matic-D2
- ZF TE ML 11A/11B, MAN 339A, Bentley, Porsche, PSA, Volvo ATFs

## Typical Properties

Test Items	Method	Unit	S-OIL 7 ATF Multi
Specific gravity	ASTM D1298	-	0.848
Color	ASTM D1500	-	Red
Viscosity 40°C	ASTM D445	cSt	36.8
Viscosity 100°C	ASTM D445	cSt	7.0
Viscosity index	ASTM D2270	-	153
Flash point	ASTM D92	°C	232
Pour point	ASTM D97	°C	-46

S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul, 04196, Korea

S-OIL 7 ATF Multi  
2015.12.15.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.