



S-OIL SEVEN LPG

FULLY SYNTHETIC LPG & GASOLINE ENGINE OIL

Product Description

S-OIL SEVEN LPG 10W-30 is made by 100% synthetic base oil, suitable for all passenger cars that run on LPG and gasoline. Also suitable for latest engine fitted new technologies including turbo-charger, DOHC, GDI and vehicles requiring performance specifications API SN, ILSAC GF-5.

Applications

- All passenger cars that run on LPG and gasoline
- Especially, suitable for vehicles driving in modern start-stop traffic conditions
- Vehicles equipped with DOHC, Turbocharger, GDI are suggested to apply API SN, ILSAC GF-5 engine oil

Features and potential benefits

- This engine oil provides premium performance thanks to very stable and clean base oil properties
- High viscosity index ensures adequate oil film strength at hot operating condition
- S-OIL SEVEN LPG is formulated with latest cleaning agents that help to remove dirt and deposits actively
- Eco-friendly engine oil with Improved fuel efficiency caused by minimization of friction in moving parts

Performance level

- API : 10W-30 (API SN/ILSAC GF-5), 10W-40 (API SN)

Typical Properties

Test Items	Method	Unit	10W-30	10W-40
Specific gravity	ASTM D1298	-	0.855	0.859
Viscosity	ASTM D445	40°C	64.7	90.40
		100°C	10.21	13.60
Viscosity index	ASTM D2270	-	144	152
Flash point	ASTM D92	°C	246	246
Pour point	ASTM D97	°C	-25	-33

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN LPG
2015.7.15.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.