



S-OIL dragon CD

MONOGRADE OIL FOR DIESEL ENGINE OIL

Product Description

DRAGON CD is suitable to normally aspirated Diesel engines of civil works machines, trucks, fishing boats, locomotives, Diesel stationary engines (energy production). It is also suitable for gear boxes, torque converters, hydraulic systems when manufacturer requires engine oil with an appropriate grade for these applications.

Applications

- All normally aspirated diesel engines for all services when the manufacturer has no special requirement.

Features and potential benefits

- High viscosity index
- Good level of detergency
- Exceptional detergency level
- High stability in operation
- Excellent antiwear and anticorrosion properties
- Excellent antioxidant, antirust and antifoaming properties.

Performance level

- API CD

Typical Properties

Test Items	Method	Unit	10W	30	40
Specific gravity	ASTM D1298	-	0.8741	0.8792	0.8846
Viscosity	40°C ASTM D445	cSt	41.5	96.7	137.7
	100°C ASTM D445	cSt	6.7	11.4	14.4
Viscosity index	ASTM D2270	-	110	105	103
Flash point	ASTM D92	°C	228	248	252
H.T.H.S viscosity	ATSM D4683	-	2.26	3.43	4.1
Pour point	ASTM D97	°C	-32.5	-22.5	-20

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

DRAGON CD
2016.12.13.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.