



BARDAHL TECHNOS C60 *exceed* 5W40 mSAPS

TECHNOS C60 *exceed* mSAPS is a PREMIUM PERFORMANCE lubricant for the latest generation of gasoline and diesel engines equipped with exhaust gas post-treatment systems requiring lubricants with low contents of SAPS.

Thanks to its specific additives, **mSAPS**, with low contents of sulphur, phosphorus and sulphated ashes, extends the life of the anti-particulate filters (FAP and DPF) and catalytic exhausts.

The precious synthetic bases and the special blending high stability polymers used in its formula, give **TECHNOS C60 *exceed*** extraordinary properties of resistance to the thermal deterioration due to oxidation, tenacity of the lubricating oil film and fluidity at low temperatures.

TECHNOS C60 *exceed* mSAPS also guarantees a superior control of deposits, sludge and wear, thus allowing the engine to offer and preserve its original maximum mechanical performance.

TECHNOS C60 *exceed* mSAPS helps to efficaciously fight against wear due to oil dilution with fuel and dirt in the engine caused by the use of bio-diesel in the gas oil.

TECHNOS C60 *exceed* mSAPS offers superior performances in comparison to traditional lubricants. Greater protection of the engine, better performances at low temperatures, better resistance of the oil to deterioration.

Properties

- Superior control of wear, even in case of contamination of the oil with the fuel
- Longer life and higher cleanliness of all parts of the engine
- It protects the operation of anti-particulate filters and catalytic exhausts
- Easy start and immediate lubrication at low temperatures. Helps fuel economy
- Its low evaporation properties help to reduce the oil consumption
- Longer intervals between oil changes
- It efficaciously fights against the premature deterioration of the oil caused by bio-diesel
- Formulated with fully synthetic bases

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045



BARDAHL TECHNOS C60 exceed 5W40 mSAPS

PERFORMANCE LEVEL

API SN-CF / ACEA A3 / MB 229.51 – 226.5 / BMW Long Life 04
VW 502.00-505.01 / FORD WSS-M2C917A / RENAULT RN0700-RN 0710
PORSCHE A40 / GM dexos 2

CHEMICAL-PHYSICAL CHARACTERISTICS

Viscosity at 40°C	90,2 cSt
Viscosity at 100°C	14,6 cSt
Density at 15°C	0,853 kg/l
Viscosity index	170
Flash point	205°C
Pour point	-45°C
T.B.N.	8,0 (mg KOH/g)

The values shown in this table are just as an indication, variable within certain tolerances

Maroil s.r.l. – Bardahl Italia

Località ponte alla Ciliegia – 55011 Marginone – Altopascio (Lucca) – Tel. 0583-28731 / Fax 0583-286542
www.bardahl.it – e-mail: info@bardahl.it – Cable address: MAROIL: CASELLA POSTALE N.32 Altopascio
Partita IVA 01583810468 – Codice Fiscale / Registro Imprese 00160000477 – Cap. Soc. € 98.800,00 – R.E.A. di Lucca n. 84045