Technical Data Sheet

Divinol Syntholight DPF 5W30

Product description

It is the perfect product to reduce variety of motor oils. In almost all modern automobile types of BMW, Mercedes, VW, Audi and other manufacturers this oil can be filled. It doesn't matter if the car is equipped with or without diesel particulate filter or catalyser. This motor oil guarantees a maximal lifespan of exhaust aftertreatment in diesel and gas engines due to its special additives. Also suitable for VW R5 and V10 TDI motors from year 01/2007. Can be deployed in LPG/CNG motors. Acccording to the manufacturer's instructions!

Specification

ACEA C3-12

Manufacturer approval

BMW Longlife-04; MB-Approval 229.51; VW 504.00/507.00 (Longlife-III)

Manufacturer performance

Porsche C 30

Characteristics

SAE Grade:	5W30
Appearance:	slightly brown, clear
Ash / Sulfate DIN 51575:	0.5 %
Colour / DIN ISO 2049:	3
Viscosity/40°C / DIN 51 562:	65 mm²/s
Viscosity/100°C / DIN 51 562:	11.5 mm²/s
Viscosity index / DIN ISO 2909:	172
Density/15°C / DIN 51 757:	0,853 g/cm³

49180

09/2014-49180-9

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.





ZG Division: Divinol Lubricants & Release Agents Zeller+Gmelin GmbH & Co. KG Schlossstr. 20 - 73054 Eislingen/Fils Tel. +49 7161 802-0 - Fax +49 7161 802-230 www.zeller-gmelin.de - dst@zeller-gmelin.de



Technical Data Sheet

Divinol Syntholight DPF 5W30

Pour point / DIN ISO 3016:	-39 °C
Flash point (Cleveland) / DIN ISO 2592:	220 °C
TBN:	6.6 mgKOH/g

Application

Almost all modern automobile types of BMW, Mercedes, VW and Audi can be filled with the product. It doesn't matter whether with or without diesel particulate filter as the case may be catalyzer. The motor oil guarantees a maximal engine life of exhaust aftertreatment in diesel and gas engine due to its special additives.

49180

09/2014-49180-9

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2/2



ZG Division: Divinol Lubricants & Release Agents Zeller+Gmelin GmbH & Co. KG Schlossstr. 20 - 73054 Eislingen/Fils Tel. +49 7161 802-0 - Fax +49 7161 802-230 www.zeller-gmelin.de - dst@zeller-gmelin.de

