

Technical Data Sheet

Divinol Syntholight 5W-50

Product description

Divinol Syntholight 5W-50 is a high-tech engine oil for the most demanding requirements. Its blend and range of additives ensures excellent protection against wear, deposits and corrosion. It saves fuel due to its low viscosity, reduces oil consumption, withstands extreme temperatures and guarantees a longer engine life.

Specification

API SL/CF; ACEA A3-08/B3-08

Characteristics

SAE Grade:	5W50
Ash / Sulfate DIN 51575:	1 %
Colour / DIN ISO 2049:	3,5
Viscosity/40°C / DIN 51 562:	115 mm ² /s
Viscosity/100°C / DIN 51 562:	18 mm ² /s
Viscosity index / DIN ISO 2909:	175
Density/15°C / DIN 51 757:	0,850 g/cm ³
Pour point / DIN ISO 3016:	-34 °C
Flash point (Cleveland) / DIN ISO 2592:	220 °C
TBN:	9 mgKOH/g

Application

High-tech engine oil for all Otto and Diesel engines including turbosupercharger.

49510

06/2014-49510-4

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1