

Technical Data Sheet

Divinol Syntholight C2 5W-30

Product description

Divinol Syntholight C2 5W-30 is a special HC-Synthetic oil for modern diesel and fuel driven motors. The formulation „Fuel Economy“ guarantees fuel saving deployment. This quality product assures fast oiling of the motor, especially during the start and warm up phase.

Additionally Divinol Syntholight C2 5W-30 can be deployed for LPG/CNG driven motors. Please see manufacturer's technical regulations.

Specification

API SN/CF; ACEA C2-12; ILSAC GF-4/5

Manufacturer performance

Fiat (Fiat 9.55535 S1), Toyota*, Honda*, Mazda*

*according service manual of OEM

Characteristics

SAE Grade:	5W30
Ash / Sulfate DIN 51575:	0.8 %
Colour / DIN ISO 2049:	3
Viscosity/40°C / DIN 51 562:	53 mm ² /s
Viscosity/100°C / DIN 51 562:	9.7 mm ² /s
Viscosity index / DIN ISO 2909:	168
Density/15°C / DIN 51 757:	0,857 g/cm ³
Pour point / DIN ISO 3016:	-36 °C
Flash point (Cleveland) / DIN ISO 2592:	224 °C
TBN:	8.2 mgKOH/g

49700

06/2015-49700-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Syntholight C2 5W-30

Application

Divinol Syntholight C2 5W-30 is recommended for Otto- and Diesel engines in Fiat, Toyota, Honda, Mazda with or without exhaust after treatment systems considering the manufacturers instructions in each case.

49700

06/2015-49700-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2