

# Technical Data Sheet

## Divinol Synthogear SL 75W-90

---

### Product description

Divinol Synthogear SL 75W-90 is a fully synthetic high-performance oil for axle drives and gear boxes. This multigrade gear oil provides prolonged oil-change intervals due to most advanced additive technology which was developed for utility vehicles. The product is ideal for use under highest mechanical and thermal stress and enables oil-change intervals of up to 500,000 km (according to the instructions of the manufacturer!)

Advantages:

- high oxidation and temperature resistance
- excellent wearing protection
- increased oil life due to improved oxidation stability
- substantial reduction of working temperatures
- increased efficiency and therefore lower fuel consumption

### Specification

API GL 4 / GL 5, MT-1, MIL-PRF-2105E, SAE J2360

### Manufacturer performance

Arvin Meritor 0-76-N; DAF (GL5); IVECO (MIL-PRF-2105E); MB-Approval 235.8; Scania STO 1:0; MAN 341 Z2, MAN 341 E3, MAN 342 S1 (drain interval 200.000 km), Mack GO-J, Renault Axle (B0032/2 Annex 3), Volvo 97312\*; Detroit Diesel DFS93K219.01; ZF TE-ML 02B/05B/07A/12B/12L/12N/16F/17B/19C/21B

\*if API GL-5 is serviceable

### Characteristics

SAE Grade:	75W-90
Appearance:	clear
Colour / DIN ISO 2049:	L 1,5
Viscosity/40°C / DIN 51 562:	110 mm <sup>2</sup> /s
Viscosity/100°C / DIN 51 562:	15.5 mm <sup>2</sup> /s

52070

05/2016-52070-17

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

# Technical Data Sheet

## Divinol Synthogear SL 75W-90

---

Viscosity index / DIN ISO 2909:	150
Density/15°C / DIN 51 757:	880 kg/m <sup>3</sup>
Pour point / DIN ISO 3016:	< -40 °C
Flash point (Cleveland) / DIN ISO 2592:	200 °C

### Application

Divinol Synthogear SL 75W-90 is suitable for use in highly stressed driving axles and gear boxes of utility vehicles as well as for maximum oil-change intervals.

52070

05/2016-52070-17

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2