

\* \* \* Section 1 - Identification \* \* \*

Material Name: EVEREST SYNTHETIC BLEND ENGINE OIL

SDS ID: 82545

Product Identifier
EVEREST SYNTHETIC BLEND ENGINE OIL

Includes Grades: 5W-20, 5W-30, 10W-30, 10W-40, 20W-50, 10W, 30, SAE 30

#### Product Code

Prefix 21

### **Synonyms**

Petroleum oil; Lube oil; Petroleum hydrocarbon; Lubricant.

### **Recommended Use**

For lubricating passenger car motors. If these products are used in combination with other products, refer to the Material Safety Data Sheet for those products.

#### **Restrictions on Use**

None known.

#### **Manufacturer Information**

US Global Petroleum 9101 W Fullerton Ave Franklin Park, IL 60131 Phone: 1-773-376-9660 www.usglobalpetroleum.com

Emergency # 1-773-376-9660

#### **Issue Date**

March 29, 2015

### **Supersedes Issue Date**

October 5, 2012

# **Original Issue Date**

October 31, 1988

# \* \* \* Section 2 - Hazard(s) Identification \* \* \*

# Classification in Accordance with 29 CFR 1910.1200.

Not hazardous according to classification criteria.

### **GHS LABEL ELEMENTS**

### Symbol(s)

None needed according to classification criteria.

# Signal Word

None needed according to classification criteria.

## Hazard Statement(s)

None needed according to classification criteria.

### Precautionary Statement(s)

### Prevention

None needed according to classification criteria.

### Response

None needed according to classification criteria.

### Storage

None needed according to classification criteria.

### **Disposal**

Dispose in accordance with all applicable regulations.

## Hazard(s) Not Otherwise Classified

Repeated exposure may cause skin dryness or cracking.

**SDS ID: 82545** 

Material Name: EVEREST SYNTHETIC BLEND ENGINE OIL

# \* \* \* Section 3 - Composition / Information on Ingredients \* \* \*

CAS	Component	Percent
64741-88-4	Petroleum distillates, solvent-refined heavy paraffinic	0-100*
64742-01-4	Residual oils (petroleum), solvent refined	0-100*
64742-57-0	Residual oils (petroleum), hydrotreated	0-100*
64742-62-7	Residual oils (petroleum), solvent dewaxed	0-100*
72623-83-7	Lubricating oils (petroleum), C>25, hydrotreated bright stock	0-100*
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	3-100*
72623-87-1	Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	0-40
178603-64-0	Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated,	0-45
	C15-30, branched and cyclic, high viscosity index	
178603-65-1	Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated,	0-45
	C20-40, branched and cyclic, high viscosity index	
178603-66-2	Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated,	0-45
	C25-55, branched and cyclic, high viscosity index	
Not Available	Mineral Oil	4-24
64742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	0-26
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	0.25-1.5

# \* \* \* Section 4 - First Aid Measures \* \* \*

### **Description of Necessary**

### **Measures Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if needed.

### Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical attention, if needed.

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Get medical attention if needed.

## Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

#### **Most Important**

# Symptoms/Effects Acute

No information on significant adverse effects.

#### **Delayed**

No information on significant adverse effects.

# Indication of Immediate Medical Attention and Special Treatment Needed, If Needed

Treat symptomatically and supportively. Call 1-800-468-1760 for additional information.

# \* \* \* Section 5 - Fire-Fighting Measures \* \* \*

# **Suitable Extinguishing Media**

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

### Unsuitable Extinguishing Media

None known.

### Specific Hazards Arising from the Chemical

Negligible fire hazard. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

### **Hazardous Combustion Products**

Decomposition and combustion materials may be toxic. Burning may produce aldehydes, hydrogen sulfide, alkyl mercaptans, sulfides, carbon monoxide, and oxides of sulfur, calcium and zinc and other unidentified organic compounds.

Page 2 of 8 Rev. 3/15

Material Name: EVEREST SYNTHETIC BLEND ENGINE OIL

### Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

### Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Keep unnecessary people away, isolate hazard area and deny entry.

SDS ID: 82545

### NFPA Ratings: Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

# \* \* \* Section 6 - Accidental Release Measures \* \* \*

# Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

### Methods and Materials for Containment and Clean Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in Section 9: Exposure Controls/Personnel Protection. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see Section 15: Regulatory Information.

# \* \* \* Section 7 - Handling and Storage \* \* \*

# **Precautions for Safe Handling**

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes.

# Conditions for Safe Storage, Including Any Incompatibilities

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Store locked up. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

# Incompatibilities

Oxidizing materials, acids, reactive halogens.

# \* \* \* Section 8 - Exposure Controls / Personal Protection \* \* \*

#### **Component Exposure Limits**

ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

# **Appropriate Engineering Controls**

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

## Individual Protective Measures, such as Personal Protective Equipment

Protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: safety glasses, gloves, lab coat, or apron.

### **Eyes/Face Protection**

Safety glasses with side shields should be worn at a minimum. Additional protection, such as goggles, face shields, or respirators may be needed depending upon anticipated use and concentrations of mists or vapors. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

#### **Skin Protection**

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber or equivalent gloves is not recommended.

Page 3 of 8 Rev. 3/15

Material Name: EVEREST SYNTHETIC BLEND ENGINE OIL

### **Respiratory Protection**

No respirator is required under normal conditions of use. Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult with a health and safety professional for specific respirators appropriate for your use.

# \* \* \* Section 9 - Physical & Chemical Properties \* \* \*

**Appearance/Odor:** Liquid, amber, petroleum odor. **pH:** Not applicable

petroleum

**Boiling Point:** 475°F (246°C) (minimum) **Melting Point:** Not available [pour point 0°F (-

18°C) (maximum)].

**SDS ID: 82545** 

**Solubility (H2O):** Insoluble **Specific Gravity:** 0.88 (water = 1)

(approximately)

**Density:** 7.3 LB/US gal (880 g/l) **Octanol/H2O Coeff.:** Not available

(approximately)

Evaporation Rate: Not available Auto Ignition Temperature: Not available

Odor Threshold: Not available Flash Point: 383°F (195°C) (minimum)

Cleveland Open Cup

LFL: Not available Viscosity: >20.5 mm<sup>2</sup>/s @ 104°F (40°C)

UFL: Not available

Vapor Pressure: less than 0.1 mmHg at 68°F

 $(20^{\circ}C)$ 

### **Other Property Information**

No information is available.

# \* \* \* Section 10 - Stability & Reactivity \* \* \*

# Reactivity

No reactivity hazard is expected.

### **Chemical Stability**

Stable under normal temperatures and pressures.

### Possibility of Hazardous Reactions

Will not polymerize.

### **Conditions To Avoid**

Avoid sparks or flame when not in use.

# **Incompatible Materials**

Avoid oxidizing agents, acids and reactive halogens.

# **Hazardous Decomposition Products**

None under normal temperatures and pressures.

# \* \* \* Section 11 - Toxicological Information \* \* \*

### **Toxicity Data and Information**

### Component Analysis - LD50/LC50

# Petroleum distillates, solvent-refined heavy paraffinic (64741-88-4)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Residual oils (petroleum), solvent refined (64742-01-4)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Residual oils (petroleum), solvent dewaxed (64742-62-7)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Oral LD50 Rat >5000 mg/kg

### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Dermal LD50 Rabbit >4480 mg/kg; Oral LD50 Rat >2000 mg/kg

Page 4 of 8 Rev. 3/15

**SDS ID: 82545** 

# Material Name: EVEREST SYNTHETIC BLEND ENGINE OIL

# Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

### **Information on Likely Routes of Exposure**

#### Inhalation

No information on significant adverse effects.

### Ingestion

May be harmful if swallowed.

#### **Skin Contact**

No information on significant adverse effects.

#### **Eve Contact**

No information on significant adverse effects.

#### **Immediate Effects**

No information on significant adverse effects.

### **Delayed Effects**

No information on significant adverse effects.

### Irritation/Corrosivity

May cause slight skin and respiratory irritation.

# **Respiratory Sensitization**

No information available for the products.

#### **Skin Sensitization**

No information available for the product.

### **Carcinogenicity Component**

#### Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

### **Germ Cell Mutagenicity**

No information available for the product.

### Teratogenicity

No information available for the product.

### **Reproductive Effects**

No epidemiological data is available for the product.

# Specific Target Organ Effects - Single Exposure

No information on significant adverse effects.

### Specific Target Organ Effects - Repeated Exposure

No information on significant adverse effects.

# **Aspiration Hazard**

No data available.

### Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

# \* \* \* Section 12 - Ecological Information \* \* \*

### **Ecotoxicity**

Harmful to aquatic life.

### Component Analysis - Ecotoxicity - Aquatic Toxicity

### Petroleum distillates, solvent-refined heavy paraffinic (64741-88-4)

Duration/Test/Species Concentration/Conditions Notes

96 Hr LC50 Oncorhynchus mykiss >5000 mg/L 48 Hr EC50 Daphnia magna >1000 mg/L

# Residual oils (petroleum), solvent refined (64742-01-4)

Duration/Test/Species Concentration/Conditions Notes

96 Hr LC50 Oncorhynchus mykiss >5000 mg/L 48 Hr EC50 Daphnia magna >1000 mg/L

Page 5 of 8 Rev. 3/15

Material Name: EVEREST SYNTHETIC BLEND ENGINE OIL

Residual oils (petroleum), solvent dewaxed (64742-62-7)

Duration/Test/Species Concentration/Conditions Notes

96 Hr LC50 Oncorhynchus mykiss >5000 mg/L 48 Hr EC50 Daphnia magna >1000 mg/L

Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Duration/Test/Species Concentration/Conditions Notes

96 Hr LC50 Lepomis macrochirus >10000 mg/L Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Duration/Test/Species Concentration/Conditions Notes

96 Hr LC50 Brachydanio rerio 79.6 mg/L [semi-static] 96 Hr LC50 Pimephales promelas 3.2 mg/L [semi-static]

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)

Duration/Test/Species Concentration/Conditions Notes

96 Hr LC50 Oncorhynchus mykiss >5000 mg/L 48 Hr EC50 Daphnia magna >1000 mg/L **Petroleum distillates, hydrotreated heavy naphthenic (64742-52-5)** 

Duration/Test/Species Concentration/Conditions Notes

96 Hr LC50 Oncorhynchus mykiss >5000 mg/L 48 Hr EC50 Daphnia magna >1000 mg/L

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Duration/Test/Species Concentration/Conditions Notes

96 Hr LC50 Pimephales promelas 1.0 - 5.0 mg/L [static]

96 Hr LC50 Pimephales promelas 10.0 - 35.0 mg/L [semi-static]

48 Hr EC50 Daphnia magna 1 - 1.5 mg/L

**Persistence and Degradability** 

No information available for the product.

**Bioaccumulation Potential** 

No information available for the product.

Mobility in Soil

No information available for the product.

**Other Adverse Effects** 

# \* \* \* Section 13 - Disposal Considerations \* \* \*

# **Disposal Methods**

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact US Global Petroleum regarding proper recycling or disposal.

These products, if discarded, are not expected to be a characteristic or listed hazardous waste. If recycled as used oil in the USA, they can be managed in accordance with the used oil exemption under 40 CFR Part 279. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of these products.

# \* \* \* Section 14 - Transport Information \* \* \*

### **Emergency Response Guide Number**

Not applicable.

DOT Shipping Name: Not regulated as a hazardous material.TDG Shipping Name: Not regulated as a dangerous good.

# \* \* \* Section 15 - Regulatory Information \* \* \*

# Volatile Organic Compounds (As Regulated)

Negligible as per U.S EPA 40 CFR 51.100(s)

Federal Regulations SARA 302/304

### **Component Analysis**

Based on the ingredient(s) listed in SECTION 3, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

Page 6 of 8 Rev. 3/15

**SDS ID: 82545** 

Material Name: EVEREST SYNTHETIC BLEND ENGINE OIL SDS ID: 82545

### SARA 311/312 Hazardous Categories

Acute Health: No Chronic Health: No Fire: No Pressure: No Reactive: No

### SARA Section 313 Component Analysis

This product does not contain any "toxic" chemical subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

### **CERCLA**

### **Component Analysis**

Based on the ingredient(s) listed in SECTION 3, this product does not contain any "hazardous substance" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

### **TSCA Inventory**

All the components of these products are listed on, or are automatically included as "naturally occurring chemical substances" on, or are exempted from the requirement to be listed on, the TSCA Inventory.

### **Component Analysis**

Component	CAS#	TSCA
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	Yes
Residual oils (petroleum), solvent refined	64742-01-4	Yes
Residual oils (petroleum), hydrotreated	64742-57-0	Yes
Residual oils (petroleum), solvent dewaxed	64742-62-7	Yes
Lubricating oils (petroleum), C>25, hydrotreated bright stock	72623-83-7	Yes
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	Yes
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	Yes
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated,	178603-65-1	Yes
C20-40, branched and cyclic, high viscosity index		
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated,	178603-66-2	Yes
C25-55, branched and cyclic, high viscosity index		
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, 178		Yes
C15-30, branched and cyclic, high viscosity index		
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	Yes
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	Yes

# **U.S. State Regulations**

None of this product's components are listed on the state lists from CA, MA, MN, NJ or PA.

No component(s) are listed under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

# **Canadian Regulations**

These products have been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

Page 7 of 8 Rev. 3/15

Material Name: EVEREST SYNTHETIC BLEND ENGINE OIL SDS ID: 82545

Component Analysis

Component	CAS#	CAN
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	DSL
Residual oils (petroleum), solvent refined	64742-01-4	DSL
Residual oils (petroleum), hydrotreated	64742-57-0	DSL
Residual oils (petroleum), solvent dewaxed	64742-62-7	DSL
Lubricating oils (petroleum), C>25, hydrotreated bright stock	72623-83-7	DSL
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	DSL
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	DSL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated,	178603-65-1	DSL
C20-40, branched and cyclic, high viscosity index		
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated,	178603-66-2	DSL
C25-55, branched and cyclic, high viscosity index		
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated,	178603-64-0	DSL
C15-30, branched and cyclic, high viscosity index		
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	DSL
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	DSL

### Canadian WHMIS Information

Not regulated.

### Component Analysis - WHMIS IDL

Not regulated.

# \* \* \* Section 16 - Other Information \* \* \*

#### **Revision Information**

Reformat to OSHA HazCom 29 CFR 1910.1200 adoption of GHS revision 3.

### Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA -Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL -Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts<sup>TM</sup> - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

#### Disclaimer

User assumes all risks incident to the use of this (these) product(s). To the best of our knowledge, the information contained herein is accurate. However, US Global Petroleum assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product(s) as supplied to the user.

End of Sheet 82545

Page 8 of 8 Rev. 3/15